## APPENDIX C Product Label Keyword Definitions, Values - VICAR Sort

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
msn_surface:application_id	The application_id (often abbreviated APID) attribute identifies the process, or source, which created the data.			
TELEMETRY. APPLICATION_PROCESS_ID	This can include information such as an identification of the instrument which generated the telemetry stream, its operating mode at the time of data acquisition, and any onboard compression of the data.  InSight Specific:  Indicates the Application ID (APID) number for this product. APID's are used to distinguish types of telemetry products. In general the APID Name should be used rather than the numeric value (see APPLICATION_PROCESS_NAME).		ASCII_NonNegative_Integer	
msn_surface:application_name	The application_name attribute provides the name associated with the source or process which created the			
TELEMETRY. APPLICATION_PROCESS_NAME	data.		ASCII_Short_String_Collapsed	
geom: <b>selected_instrument_id</b>	The selected_instrument_id attribute specifies an abbreviated name or acronym that identifies the selected instrument mounted on the articulation device.	1)/Product Observational/Observation Area/Discipline Area/Geometr lected instrument id	y/Geometry Lander/Articulation Device Parameters[1]/se	
ARM_ARTICULATION_STATE. InSight Space ARTICULATION_DEV_INSTRUMENT_ID The values	InSight Specific: The values for InSight are BLADE_1, BLADE_2, SCOOP, IDC, WRIST, GRAPPLE, GRAPPLE_ATTACH, SEIS, WTS, HP3, and		ASCII_Short_String_Collapsed	
geom:x_unit	The x component of a unit Cartesian vector.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE		
ARM_ARTICULATION_STATE. ARTICULATION_DEV_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVO _Model/Vector_Optical/x_unit		
		3)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Axis/x unit	y/Geometry Lander/Camera Model Parameters/CAHV M	
		4)/Product Observational/Observation Area/Discipline Area/Geometr ctor Device Gravity/x unit	y/Geometry Lander/Articulation Device Parameters[1]/Ve	
		5)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector Axis/x unit	y/Geometry Lander/Camera Model Parameters/CAHVOR	
6)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Model/Vector Optical/x unit		y/Geometry Lander/Camera Model Parameters/CAHVOR		
			ASCII_Real	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom: <b>y_unit</b>	The y component of a unit Cartesian vector.	1)/Product_Observational/Observation_Area/Discipline_Area/Geometry/Geometry_Lander/Camera_Model_Parameters/CAHVORE Model/Vector_Axis/y_unit_		
ARM_ARTICULATION_STATE. ARTICULATION_DEV_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAH Model/Vector Optical/y unit		
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parame odel/Vector Axis/y unit		
		4)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Articulation Device Pactor Device Gravity/y unit		
		5)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Axis/y unit	y/Geometry Lander/Camera Model Parameters/CAHVOR	
		6)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector Optical/y unit	y/Geometry Lander/Camera Model Parameters/CAHVOR	
			ASCII_Real	
geom: <b>z_unit</b>	The z component of a unit Cartesian vector.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVO Model/Vector Axis/z unit		
ARM_ARTICULATION_STATE. ARTICULATION_DEV_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector_Optical/z_unit	y/Geometry Lander/Camera Model Parameters/CAHVORE	
		3)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Axis/z unit	y/Geometry Lander/Camera Model Parameters/CAHV M	
		4)/Product Observational/Observation Area/Discipline Area/Geometre ctor Device Gravity/z unit	y/Geometry Lander/Articulation Device Parameters[1]/Ve	
		5)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Axis/z unit	y/Geometry Lander/Camera Model Parameters/CAHVOR	
		6)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector Optical/z unit	y/Geometry Lander/Camera Model Parameters/CAHVOR	
			ASCII_Real	
geom:index_value_angle	The index_value_angle attribute provides the value of an angle as named by the associated index_id, index_name, or index_sequence_number.			
ARM_ARTICULATION_STATE. ARTICULATION_DEVICE_ANGLE ARM_ARTICULATION_STATE. ARTICULATION_STATE.	InSight Specific:  Values are in radians.		ASCII_Real	
ARTICULATION_DEVICE_ANGLEUNIT			Units_of_Angle	
	The device_id attribute specifies the abbreviated identification of an articulation device.	1)/ <u>Product_Observational/Observation_Area/Discipline_Area/Geometrouse_id</u>	y/Geometry_Lander/Articulation_Device_Parameters[*]/de	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom:device_id  *_ARTICULATION_STATE. ARTICULATION_DEVICE_ID	InSight Specific: On InSight the ids are 'IDA' for the arm and 'GRAPPLE' for the grapple.		ASCII_Short_String_Collapsed	
geom:device_mode  GRAPPLE_ARTICULATION_STATE.  ARTICULATION_DEVICE_MODE	The device_mode attribute specifies the deployment state (i.e., physical configuration) of an articulation device at the time of data acquisition. Examples include 'Arm Vibe', 'Deployed', 'Free Space', 'Stowed'. Note: the value set for this attribute is mission-specific and should be declared in a mission-specific dictionary.  InSight Specific:  State of the grapple fingers. The value is determined by the IDA FSW by reading the state of the two limit switches on the grapple. It affects when the grapple opening algorithm completes. Bit 0 is the 'fingers closed' switch, with 0=fingers-not-closed and 1=fingers-open and 1=fingers-not-open. This translates to the 4 states in the valid values list: OPEN, BROKEN, IN_BETWEEN, CLOSED. There is no mode for the IDA (arm) articulation device.	1)/Product Observational/Observation Area/Discipline Area/Geometryice mode	y/Geometry Lander/Articulation Device Parameters[2]/de  ASCII_Short_String_Collapsed	
geom:device_name  GRAPPLE_ARTICULATION_STATE.  ARTICULATION_DEVICE_NAME	The device_name attribute specifies the common name of an articulation device.  InSight Specific: On InSight the names are 'INSTRUMENT_DEPLOYMENT_ARM' and 'GRAPPLE'.	1)/Product_Observational/Observation_Area/Discipline_Area/Geometr_ vice_name	y/Geometry_Lander/Articulation_Device_Parameters[*]/de  ASCII_Short_String_Collapsed	
geom:device_phase  GRAPPLE_ARTICULATION_STATE.  ARTICULATION_DEVICE_PHASE	The device_phase attribute specifies the current phase of the mission, from an articulation-device-centric point of view.  InSight Specific: Current mission phase from a grapple-centric perspective. This affects whether the IDA_OPEN_GRAPPLE command is accepted (only in OK_TO_OPEN phase), and the assumed force on the end of the arm (based on which instrument the phase says is grappled) during arm deflection computation. Only human operators (via spacecraft command) can change this value. Valid values are LAUNCH_LOCKED, STOWED, OK_TO_OPEN, SEIS_GRAPPLED, WTS_GRAPPLED, HP3_GRAPPLED.	1)/Product Observational/Observation Area/Discipline Area/Geometrovice phase	y/Geometry Lander/Articulation Device Parameters[2]/de  ASCII_Short_String_Collapsed	
geom:index_value_temperature  *_ARTICULATION_STATE. ARTICULATION_DEVICE_TEMP  *_ARTICULATION_STATE. ARTICULATION_DEVICE_TEMPUNIT	The index_value_temperature attribute provides the value of a temperature as named by the associated index_id or index_name.	1)/Product Observational/Observation Area/Discipline Area/Geometr vice_Temperature/Device_Temperature_Index/index_value_temperature_temper		
img:auto_exposure_data_cut  OBSERVATION_REQUEST_PARMS. AUTO_EXPOSURE_DATA_CUT	The auto_exposure_data_cut attribute specifies the DN value which a specified fraction of pixels is permitted to exceed. The fraction is specified using the auto_exposure_data_fraction attribute.	1)/Product Observational/Observation Area/Discipline Area/Imaging/posure data cut	Commanded Parameters/Exposure/Autoexposure/auto_ex  ASCII_Integer	
	The auto_exposure_percent attribute specifies the auto- exposure early-termination percent. If the desired DN	1)/Product Observational/Observation Area/Discipline Area/Imaging/posure_percent	Commanded Parameters/Exposure/Autoexposure/auto ex	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:auto_exposure_percent  OBSERVATION_REQUEST_PARMS.  AUTO_EXPOSURE_PERCENT	(auto_exposure_data_cut) is within this percentage of the measured DN (the DN at which the percentage of pixels above that DN equals or exceeds the auto_exposure_pixel_fraction), then the auto exposure algorithm is terminated and the calculated time is accepted.		ASCII_Real
img:auto_exposure_pixel_fraction	The auto_exposure_pixel_fraction attribute specifies the percentage of pixels whose DN values may exceed the	1)/Product Observational/Observation Area/Discipline Area/Imaging/posure pixel fraction	Commanded Parameters/Exposure/Autoexposure/auto_ex
OBSERVATION_REQUEST_PARMS. AUTO_EXPOSURE_PIXEL_FRACTION	auto_expsoure_data_cut.		ASCII_Real
img:sample_fov	The sample_fov attribute specifies the angular measure of	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Subframe/sample_fov	
INSTRUMENT_STATE_PARMS. AZIMUTH_FOV INSTRUMENT_STATE_PARMS. AZIMUTH_FOVUNIT	the field of view of an imaged scene, as measured in the image sample direction (generally horizontal).  InSight Specific:  Computed by projecting rays from the left and right edges of the image at the center through the camera model, and computing the angle subtended by those rays.		ASCII_Real  Units_of_Angle
img:color_filter_array_type	Defines the type of Color Filter Array (CFA) used to encode	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Filter Array/color filter array type	
INSTRUMENT_STATE_PARMS. <b>CFA_TYPE</b>	multiple colors in a single exposure. The most common example of this is the Bayer pattern. This is optional if there is no CFA. Additional attributes, specific to each CFA type, define whether or not the CFA pattern has been removed, and if so, how (e.g. bayer_algorithm).	1) Bayer RGGB	ASCII_Short_String_Collapsed
img:color_space	Defines the color space in which this product is expressed.	-11	
DERIVED_IMAGE_PARMS. COLOR_SPACE	Some color spaces (e.g. XYZ or xyY) are independent of illuminant, while for others (e.g. sRGB or pRGB) the illuminant matters. It is expected that the defined color spaces will increase over time.	1) iRGB 2) sRGB 3) pRGB 4) wRGB 5) CIE_XYZ 6) CIE_xyY 7) HSI	ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
*_COORDINATE_SYSTEM.  *_COORDINATE_SYSTEM_INDEX  *_COORDINATE_SYSTEM_INDEX_NAME	Identifies a coordinate space using an index value given in an identified list.  InSight Specific:  InSight uses coordinate space indices of 'SITE' and 'DRIVE'.  Although InSight is not supposed to move once landed, these are included for compatibility with other Mars surface missions.	1)/Product Observational/Observation Area/Discipline Area/Surface eference/Coordinate Space Indexed/Coordinate Space Indexed/Surface Indexed/Surf	maging/Derived_Product_Parameters/Coordinate_Space_R  chy/Spatial_Reference_Information/Horizontal_Coordinate_Reference/Coordinate_Space_Indexed/Coordinate_Space_In  chy/Spatial_Reference_Information/Horizontal_Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Reference/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed/Coordinate_Space_Indexed_Indexe	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom:coordinate_space_frame_type  LANDER_COORDINATE_SYSTEM. COORDINATE_SYSTEM_NAME ARM_COORDINATE_SYSTEM. COORDINATE_SYSTEM_NAME SITE_COORDINATE_SYSTEM. COORDINATE_SYSTEM_NAME	The coordinate_space_frame_type attribute identifies the type of frame being described, such as SITE, LOCAL_LEVEL, LANDER, ROVER, ARM, etc. When combined with Coordinate_Space_Index and the optional solution_id in the Coordinate_Space_Indexed class, this serves to fully name an instance of a coordinate space.  InSight Specific:  Coordinate systems used by the InSight pipeline are Site, Lander, and Arm.	1)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Space R		
proc:program_start_date_time	The program_start_date_time specifies the datetime for the start of the software program execution.	1)/Product Observational/Observation Area/Discipline Area/Processin ogram start date time	Information/Process/Software/Software Program[*]/pr	
*. DAT_TIM		2)/Product Observational/Observation Area/Discipline Area/Processing am start date time	ng Information/Process/Software/Software Program/progr	
			ASCII_Date_Time_YMD_UTC	
img_surface:derived_image_type_name	The derived_image_type_name attribute specifies how to interpret the pixel values in a derived image (or			
DERIVED_IMAGE_PARMS. DERIVED_IMAGE_TYPE	colloquially, the type of the derived image itself). Valid values vary per mission depending on the products produced.  InSight Specific:  Additional types may be added throughout the mission. See the SIS for a table of current valid values.		ASCII_Short_String_Collapsed	
img:erase_count	The erase_count specifies the number of times a detector	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	Commanded Parameters/Detector/erase_count	
has been or will be flushed of data in raw counts, dependent on the parent class for the attribute.  InSight Specific: Number of fast flushes			ASCII_NonNegative_Integer	
		1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/		

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
img:detector_to_image_rotation  INSTRUMENT_STATE_PARMS.  DETECTOR_TO_IMAGE_ROTATION	The detector_to_image_rotation attribute specifies the clockwise rotation, in degrees, that was applied to an image along its optical path through an instrument, from detector to final image orientation.  InSight Specific:  The IDC EDR is rotated 270 degrees, so the arm/grapple is at the top of the image. The ICC requires no rotation.		ASCII_Real  Units_of_Angle	
msn_surface:download_priority  TELEMETRY. DOWNLOAD_PRIORITY	The download_priority attribute specifies which data to downlink/transmit, based on order of importance. The lower numerical priority (higher-ranked number) data products are transmitted before higher numerical priority (lower-ranked number) data products. For example, an image with a downlink priority of 1 will be transmitted before an image with a downlink priority of 6. Value of 0 specifies use of on-board default.  InSight Specific:  Values are 1-6 for InSight.		ASCII_NonNegative_Integer	
msn_surface:earth_received_start_date_time  TELEMETRY. EARTH_RECEIVED_START_TIME	The earth_received_start_date_time attribute provides the earliest time at which any component telemetry data for a particular product was received.		ASCII_Date_Time_YMD_UTC	
msn_surface:earth_received_stop_date_time	The earth_received_stop_date_time attribute provides the latest time at which any component telemetry data for a			
TELEMETRY. EARTH_RECEIVED_STOP_TIME	particular product was received.		ASCII_Date_Time_YMD_UTC	
img:line_fov	The line_fov attribute specifies the angular measure of the field of view of an imaged scene, as measured in the image	1)/Product Observational/Observation Area/Discipline Area/Imaging/Subframe/line fov		
INSTRUMENT_STATE_PARMS. ELEVATION_FOV INSTRUMENT_STATE_PARMS. ELEVATION_FOVUNIT	line direction (generally vertical).  InSight Specific:  Computed by projecting rays from the top and bottom edges of the image at the center through the camera model, and computing the angle subtended by those rays.		ASCII_Real  Units_of_Angle	
img:encoded_display_gamma	Defines the gamma value encoded in this image. Gamma correction is used to nonlinearly compress the intensities	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Processing/encoded display gamma	
DERIVED_IMAGE_PARMS. ENCODED_DISPLAY_GAMMA	in an image, and most display systems assume that images are encoded with an sRGB gamma. Note that this is a string value because the most common gamma correction ("sRGB") is not precisely expressible as a gamma exponent. A numeric value indicates a gamma exponent.		ASCII_Short_String_Collapsed	
img_surface:Error_Model	The Error_Model class specifies the name of the error model used, a reference to the algorithm descriptions, and the parameters needed for that algorithm. The specific set	1) img_surface:error_model_name		
DERIVED_IMAGE_PARMS.  ERROR_MODEL_DESCPTR	of values is determined by each individual missions.	2) imq surface:Error Model Parameter 3) Internal Reference		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Unit</i> s
img_surface:error_model_name  DERIVED_IMAGE_PARMS. ERROR_MODEL_NAME	The error_model_name attribute specifies the method or algorithm used to create the error estimate. Each mission will define their own set of possible values. Algorithms will be added over time. The initial value is MIPL_CONST_DISPARITY_PROJECTED_V1, which means an arbitrary constant disparity error is assumed (in ERROR_MODEL_PARMS), which is projected through the camera models to approximate an error ellipse, which is then projected to the XYZ or range/crossrange axes depending on the file type.  InSight Specific:  The only error model used by the InSight pipeline is MIPL_CONST_DISPARITY_PROJECTED_V1, which projects a constant disparity into XYZ space to determine the error.		ASCII_Short_String_Collapsed
msn_surface: <b>expected_packets</b>	The expected_packets attribute provides the total number of telemetry packets which constitute a complete data		
TELEMETRY. <b>EXPECTED_PACKETS</b>	product, i.e., a data product without missing data.		ASCII_NonNegative_Integer
img:exposure_count	The exposure count attribute provides the number of exposures taken during a certain interval, such as the	1)/Product Observational/Observation Area/Discipline Area/Imaging/Exposure/exposure count	
INSTRUMENT_STATE_PARMS. EXPOSURE_COUNT	duration of one command. For example, this may include the number of exposures needed by an autoexpose		ASCII_NonNegative_Integer
img:exposure_duration	The exposure_duration attribute provides the amount of time the instrument sensor was gathering light from the	1)/Product Observational/Observation Area/Discipline Area/Imaging/Exposure/exposure duration	
INSTRUMENT_STATE_PARMS.  EXPOSURE_DURATION INSTRUMENT_STATE_PARMS.  EXPOSURE_DURATIONUNIT	scene, such as between opening and closing of a shutter, or between flushing and readout of a CCD.		ASCII_Real  Units_of_Time
img:exposure_duration_count	The exposure_duration_count attribute specifies the value, in raw counts, for the amount of time the	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Exposure/exposure_duration_count	
OBSERVATION_REQUEST_PARMS. EXPOSURE_DURATION_COUNT	instrument sensor was gathering light from the scene, such as between opening and closing of a shutter, or between flushing and readout of a CCD. This is the raw count either	2)/Product Observational/Observation Area/Discipline Area/Imaging/Commanded Parameters/Exposure/exposure duration of unt	
commanded or taken directly from telemetry as reported by the spacecraft. This attribute is the same as the exposure_duration but in DN counts instead of time, and the translation of exposure_duration_count to exposure_duration will differ by mission.  InSight Specific:  For InSight, the factor is 6.21 msec/DN.		ASCII_NonNegative_Integer	
img:exposure_type			Commanded Parameters/Exposure/exposure type
on a camera. Valid values: 'Manual' - manual exposure setting, 'Auto' - autoexposure is applied by the camera, 'Test' - test exposure setting telling the camera to return a fixed-pattern test image.	1) Manual 2) Auto 3) Test	ASCII_Short_String_Collapsed	
		1)/Product Observational/Observation Area/Discipline Area/Imaging,	/ <u>Subframe/first_line</u>

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:first_line  IMAGE_DATA. FIRST_LINE	The first_line attribute indicates the line within a source image that corresponds to the first line in a sub-image.  InSight Specific:  InSight does not support subframing, so this value is always  1.		ASCII_NonNegative_Integer
img:first_sample	The first_sample attribute indicates the sample within a source image that corresponds to the first sample in a sub-	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	Subframe/first_sample
IMAGE_DATA. FIRST_LINE_SAMPLE	image.  InSight Specific:  InSight does not support subframing, so this value is always  1.		ASCII_NonNegative_Integer
msn_surface:flight_software_version_id	The flight_software_version_id attribute identifies the version of the instrument flight software used to acquire		
TELEMETRY. FLIGHT_SOFTWARE_VERSION_ID	the image.		ASCII_Short_String_Collapsed
data_type	The data_type attribute provides the hardware representation used to store a value in Element_Array.	1)/Product Collection/File Area Inventory/Inventory/Record Delimited/Field Delimited[*]/data_type	
SYSTEM. <b>FORMAT</b>		2)/Product Observational/File Area Observational/Table Delimited[*]/Record Delimited/Field Delimited[*]/data type  3)/Product Observational/File Area Observational/Array 2D Image/Element Array/data type  4)/Product Observational/File Area Observational/Array 3D Image/Element Array/data type	
		1) ComplexLSB16 2) ComplexLSB8 3) ComplexMSB16 4) ComplexMSB8 5) IEEE754LSBDouble 6) IEEE754LSBSingle 7) IEEE754MSBDouble 8) IEEE754MSBSingle 9) SignedBitString 10) SignedByte 11) SignedLSB2 12) SignedLSB4 13) SignedLSB8 14) SignedMSB2 15) SignedMSB8 16) SignedMSB8 17) UnsignedBitString 18) UnsignedBitString 18) UnsignedBitString 20) UnsignedLSB2 21) UnsignedLSB2 22) UnsignedLSB8 22) UnsignedMSB8 23) UnsignedMSB2 23) UnsignedMSB8	ASCII_Short_String_Collapsed
			Frame/frame_id

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:frame_id  IDENTIFICATION. FRAME_ID	The frame_id attribute specifies an identification for a particular instrument measurement frame. A frame consists of a sequence of measurements made over a specified time interval, and may include measurements from different instrument modes. These sequences repeat from cycle to cycle and sometimes within a cycle.  InSight Specific:  Used to denote the commanded camera eye for stereo. InSight has no stereo camera but the IDC is commanded with some images marked 'left' and 'right' for ease of stereo processing. Note that any given image can be used either as a left or right eye image in special processing; this value reflects only the commanded intent (via IMAGE_ID).		ASCII_Short_String_Collapsed
img:frame_type_name	The frame_type_name attribute specifies whether the	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Frame/frame_type_name
IDENTIFICATION. FRAME_TYPE	image was commanded as part of a stereo pair or as a single left or right monoscopic image. If frame_type = 'Stereo', a left and a right image should be present.		ASCII_Short_String_Collapsed
img_surface:geometry_projection_type	The geometry_projection_type attribute specifies how pixels in a file have been reprojected to correct for camera	ra .	
IDENTIFICATION.  GEOMETRY_PROJECTION_TYPE	distortion, linearization, or rubber-sheeting (it is not the intent of this field to capture map projections). "Raw" indicates no projection has been done.  InSight Specific:  RAW means the image uses a CAHVOR or CAHVORE camera model. LINEARIZED means that reprojection has been performed to linearize the camera model (thus removing things like lens distortion). This means the image uses a CAHV camera model.	1) Raw 2) Linearized	ASCII_Short_String_Collapsed
msn_surface: <b>surface_gravity</b>	The surface_gravity attribute specifies the acceleration of gravity (magnitude, not direction).		
ARM_ARTICULATION_STATE.  GRAVITY_ACCELERATION	Bravity (magnitude, not direction).		ASCII_Real  Units_of_Acceleration
img:illuminant	Defines the illuminant that was used in order to process	-//	
DERIVED_IMAGE_PARMS. ILLUMINANT	this image. The valid values are open-ended but examples of valid values include: None, D65, 3000K, 5000K.		ASCII_Short_String_Collapsed
msn_surface:data_size	The data_size specifies number of bytes in the compressed data stream, not including headers.	sed	
TELEMETRY. <b>IMAGE_DATA_SIZE</b>	,,		ASCII_NonNegative_Integer
-			-

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img_surface: <b>image_id</b> IDENTIFICATION. <b>IMAGE_ID</b>	The image_id is an arbitrary string identifier that is associated with this image. The specific interpretation of it is mission-dependent, and it need not be unique to this image. For example, missions may use it as an image counter, a round-trip token indicating how to process the image, or a FSW-assigned value identifying the image.  Insight Specific:  The image_id is a 32-bit integer token set in the command sent from the ground, and returned in the image telemetry. It contains five subfields, each of which has its own label attributes: sequence_id, mesh_id, mosaic_id, stereo_id, and camera eye (frame_id). See each attribute for its usage. 'Note that image_id values are not unique (multiple images may share the same ID).		ASCII_Short_String_Collapsed
img_surface:image_type  IDENTIFICATION. IMAGE_TYPE	The image_type attribute specifies the type of image acquired. The intent is to distinguish between different kinds of image-related data that may differ in how they are interpreted. Some types are not standard images, but they are stored in an image structure. Examples include Regular, Thumbnail, Reference Pixels, Histogram, Row Sum, and Column Sum.	1) REGULAR 2) THUMBNAIL 3) REF_PIXELS 4) HISTOGRAM 5) ROW_SUM 6) COL_SUM 7) SPECTRA 8) HEALTH	ASCII_Short_String_Collapsed
proc:Input_Product  DERIVED_IMAGE_PARMS. INPUT_PRODUCT_ID	The Input_Product class describes one of the product most directly used as input to software for product creation, including raw, partially-processed, calibrated, or derived products.	1)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product  2)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product  1)   local   identifier 2)   External   Reference	
img:color_subsampling_mode  COMPRESSION_PARMS. INST_CMPRS_COLOR_MODE	The color_subsampling_mode attribute specifies the JPEG color subsampling mode used during compression. Valid values: '4:2:2' - 4:2:2 chroma subsampling, which is the typical case, '4:4:4' - 4:4:4 chroma sampling, which indicates no subsampling, 'Grayscale' - indicates a grayscale image InSight Specific:  Note that the VICAR valid values are different from PDS 4 but mean the same: COLOR_MODE_GRAY, COLOR_MODE_422, COLOR_MODE_444	3) Internal_Reference  1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/ng_mode  1) 4:4:4 2) 4:2:2 3) Grayscale	Onboard Compression/JPEG Parameters/color_subsampli  ASCII_Short_String_Collapsed
img:onboard_compression_type  COMPRESSION_PARMS. INST_CMPRS_NAME	The onboard_compression_type attribute identifies the type of on-board compression used for data storage and transmission. Valid Values: 'ICER', 'LOCO', 'JPEG', 'JPEG Progressive', 'MSSS Lossless', 'None'.  InSight Specific:  Almost all images will be JPEG. The only other option is None, which is unlikely to be used outside of instrument calibration and checkout.	1)/Product Observational/Observation Area/Discipline Area/Imaging/  1) ICER 2) ICT 3) LOCO 4) JPEG 5) JPEG Progressive 6) MSSS Lossless 7) None	Onboard Compression/onboard compression type  ASCII_Short_String_Collapsed
		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Onboard_Compression/JPEG_Parameters/jpeg_quality

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:jpeg_quality  COMPRESSION PARMS. INST_CMPRS_QUALITY	The jpeg_quality attribute is a JPEG specific variable which identifies the resultant or targeted image quality index for on-board data compression.		ASCII_NonNegative_Integer
img:onboard_compression_rate	The onboard compression rate attribute provides the	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Onboard Compression/onboard compression rate
COMPRESSION_PARMS. INST_CMPRS_RATE	average number of bits needed to represent a pixel for image that was compressed on-board for data storage and transmission.  InSight Specific:  Represents actual results (not commanded value)		ASCII_Real
img:onboard_compression_ratio	The onboard_compression_ratio attribute provides the	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	Onboard_Compression/onboard_compression_ratio
COMPRESSION_PARMS. INST_CMPRS_RATIO	ratio of the size, in bytes, of the original uncompressed data object to its compressed form (original size / compressed size). Onboard compression is performed for data storage and transmission.  InSight Specific:  Represents actual results (not commanded value)		ASCII_Real
geom:instrument_azimuth	The instrument_azimuth attribute specifies the value for an instrument's rotation in the horizontal direction. It may be measured from a low hard stop, or relative to a	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived Geometry[*]/instrument azi muth	
SITE_DERIVED_GEOMETRY_PARMS. INSTRUMENT_AZIMUTH SITE_DERIVED_GEOMETRY_PARMS. INSTRUMENT_AZIMUTH_UNIT	coordinate frame. Although it may be used for any instrument where it makes sense, it is primarily intended for use in surface-based instruments that measure pointing in terms of azimuth and elevation. If this value is expressed using a coordinate system, the coordinate system is specified by the Coordinate_Space_Reference class. The interpretation of exactly what part of the instrument is being pointed is mission-specific. It could be the boresight, the camera head direction, the CAHV camera model A vector direction, or any of a number of other things. As such, for multimission use this value should be used mostly as an approximation, e.g. identifying scenes which might contain a given object.  Insight Specific:  The interpretation is the boresight of the camera, defined as projecting the center of the nominal image (before downsampling or subframing) through the camera model. Azimuth is measured in Site frame.		ASCII_Real  Units_of_Angle
	The instrument_elevation attribute specifies the value for an instrument's rotation in the vertical direction. It may be	1)/Product Observational/Observation Area/Discipline Area/Geometrosation	y/Geometry Lander/Derived Geometry[*]/instrument ele

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:instrument_elevation  SITE_DERIVED_GEOMETRY_PARMS. INSTRUMENT_ELEVATION SITE_DERIVED_GEOMETRY_PARMS. INSTRUMENT_ELEVATIONUNIT	usually measured from a low hard stop, or relative to a coordinate frame. Although it may be used for any instrument where it makes sense, it is primarily intended for use in surface-based instruments that measure pointing in terms of azimuth and elevation. If this value is expressed using a coordinate system, the coordinate system is specified by the Coordinate_Space_Reference class. The interpretation of exactly what part of the instrument is being pointed is mission-specific. It could be the boresight, the camera head direction, the CAHV camera model A vector direction, or any of a number of other things. As such, for multimission use this value should be used mostly as an approximation, e.g. identifying scenes that might contain a given object. InSight Specific:  The interpretation is the boresight of the camera, defined as projecting the center of the nominal image (before downsampling or subframing) through the camera model. Elevation is measured in Site frame.		ASCII_Real  Units_of_Angle

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>	
lid_reference	The lid_reference attribute provides the logical_identifier for a product.	1)/Product Collection/Context Area/Investigation Area/Internal Reference/lid reference		
IDENTIFICATION. INSTRUMENT_ID		2)/Product Collection/Context Area/Observing System/Observing System Component[*]/Internal Reference/lid reference		
		3)/Product_Collection/Context_Area/Target_Identification/Internal_Re	rference/lid_reference	
		4)/Product_Collection/Reference_List/Internal_Reference[*]/lid_refere	ence	
		5)/Product_Document/Reference_List/Internal_Reference[*]/lid_reference	<u>ence</u>	
		6)/Product Document/Context Area/Investigation Area/Internal Refe	erence/ <u>lid_reference</u>	
		7)/Product_Document/Context_Area/Observing_System/Observing_Sy	rstem_Component/Internal_Reference/lid_reference	
		8)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Geometry Projection/Internal Reference/lid_reference  9)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Stereo_Product_Parameters/Internal_Reference/lid_reference  10)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Placement Target Instrument/Internal_Reference/lid_reference		
		11)/Product Observational/Observation Area/Discipline Area/Imaging id reference	g/Flat_Field_Correction/Flat_Field_File/Internal_Reference/I	
		12)/Product Observational/Observation Area/Investigation Area/Inte	ernal_Reference/lid_reference	
		13)/Product Observational/Observation Area/Observing System/Observe	erving System Component[*]/Internal Reference/lid refer	
		14)/Product Observational/Observation Area/Target Identification/In	nternal_Reference/lid_reference	
		15)/Product_Browse/Reference_List/Internal_Reference/lid_reference		
			ASCII_LID	
img_surface:ops_instrument_key	The ops_instrument_key attribute specifies the identifier or key for the instrument that was used during operations			
IDENTIFICATION. INSTRUMENT_ID	to look up instrument parameters or calibration.		ASCII_Short_String_Preserved	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img_surface:instrument_mode_id  INSTRUMENT_STATE_PARMS. INSTRUMENT_MODE_ID	The instrument_mode_id attribute provides an instrument-dependent designation of operating mode. This may be simply a number, letter or code, or a word such as 'normal', 'full resolution', 'near encounter', or 'fixed grating'. These types may vary by mission so the permissible values should be set by the mission dictionaries.  InSight Specific: For InSight the value is always 'FULL_FRAME'.		ASCII_Short_String_Collapsed
img_surface:instrument_serial_number	The instrument serial number element provides the manufacturer's serial number assigned to an instrument.		
IDENTIFICATION. INSTRUMENT_SERIAL_NUMBER	This number may be used to uniquely identify a particular instrument for tracing its components or determining its calibration history, for example.		ASCII_Short_String_Collapsed
img:temperature_value	The temperature_value attribute provides the temperature, in the specified units, of some point on an imaging instrument or other imaging instrument device.	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/ure[*]/temperature_value	Instrument_State/Device_Temperatures/Device_Temperat
INSTRUMENT_STATE_PARMS. INSTRUMENT_TEMPERATURE	magnig instrument of other imagnig instrument device.		ASCII_Real
INSTRUMENT_STATE_PARMS. INSTRUMENT_TEMPERATUREUNIT			Units_of_Temperature
img:device_id	The device_id attribute supplies the identifier of an imaging instrument, an imaging instrument device, or some point on the instrument or device.	1)/Product Observational/Observation_Area/Discipline_Area/Imaging/Instrument_State/Device_Temperatures/Device_Temperature[*]/device_id	
INSTRUMENT_STATE_PARMS. INSTRUMENT_TEMPERATURE_NAME	some point on the instrument or device.  InSight Specific:  On InSight this is used to describe camera temperatures.  Values are 'IDC_CCD', 'IDC_ELECTRONICS', 'ICC_CCD', and 'ICC_ELECTRONICS'.		ASCII_Short_String_Collapsed
img_surface:instrument_type	The instrument_type attribute specifies the type of an instrument, for example IMAGING CAMERA,		
IDENTIFICATION. INSTRUMENT_TYPE	SPECTROMETER, IMAGING SPECTROMETER, RADIOMETER, etc. InSight Specific: For InSight cameras, the value is always 'IMAGING CAMERA'		ASCII_Short_String_Collapsed
img_surface:instrument_version_number	The instrument_version_number element identifies the specific model of an instrument used to obtain data. For		
IDENTIFICATION. INSTRUMENT_VERSION_ID	example, this keyword could be used to distinguish between an engineering model of a camera used to acquire test data, and a flight model of a camera used to acquire science data during a mission.  InSight Specific: For InSight the value is 'EMC' for engineering model, 'FMC' for flight model, or 'SIM' for the simulator.		ASCII_Short_String_Collapsed
invalid_constant	The invalid_constant attribute provides a value that indicates the original value was outside the valid range for	1)/Product Observational/File Area Observational/Array 2D Image/Special Constants/invalid constant or	
IMAGE_DATA. <b>INVALID_CONSTANT</b>	the parameter.  InSight Specific:  The value should be 0.0 for most MIPL-generated products.  No distinction is generally made between invalid and missing data.	2)/Product Observational/File Area Observational/Array 3D Image/S	pecial Constants/invalid constant
			ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
offset	The offset attribute provides the displacement of the object starting position from the beginning of the parent	1)/Product Collection/File Area Inventory/Inventory/offset		
SYSTEM. LBLSIZE	structure (file, record, etc.). If there is no displacement, offset=0.  2)/Product Observational/File Area Observational/Table Delimited[*]/offset		/offset	
		3)/Product Observational/File Area Observational Supplemental[1]/Stream Text/offset		
		4)/Product_Observational/File_Area_Observational_Supplemental[*]/E	ncoded_Image/offset	
		5)/Product XML Schema/File Area XML Schema[*]/XML Schema/off	<u>set</u>	
		6)/Product File Text/File Area Text/Stream Text/offset		
		7)/Product Observational/File Area Observational/Array 2D Image/o	ffset	
		8)/Product Observational/File Area Observational/Header/offset		
		9)/Product_Observational/File_Area_Observational/Array_3D_Image/offset		
		10)/Product Observational/File Area Observational Supplemental/En	coded_Image/offset	
		11)/Product Browse/File Area Browse/Encoded Image/offset		
			ASCII_NonNegative_Integer	
			Units_of_Storage	
object_length	The object_length attribute provides the length of the digital object in bytes.	1)/Product Observational/File Area Observational/Header/object len	gth	
SYSTEM. LBLSIZE			ASCII_NonNegative_Integer	
			Units_of_Storage	
img:samples	The samples attribute indicates the total number of data instances along the horizontal axis of an image or sub-	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Subframe/samples	
IMAGE_DATA. LINE_SAMPLES	image.		ASCII_NonNegative_Integer	
img_surface:linearization_mode_fov	The linearization_mode_fov attribute specifies how the linearized camera model's field of view (FOV) as			
DERIVED_IMAGE_PARMS. LINEARIZATION_MODE	constructed (corresponding to the "cahv_fov" parameter in MIPL software).  InSight Specific: On InSight, Nominal mode is not available.	1) Min 2) Max 3) Linear 4) None	ASCII_Short_String_Collapsed	
img: <b>lines</b>	The lines attribute indicates the total number of data instances along the vertical axis of an image or sub-image.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Subframe/lines		
IMAGE_DATA. <b>LINES</b>			ASCII_NonNegative_Integer	
		1)/Product Observational/Observation Area/Time Coordinates/local mean solar time		

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
local_mean_solar_time	The local_mean_solar_time attribute provides the hour angle of the fictitious mean Sun at a fixed point on a		ASCII_Short_String_Collapsed	
IDENTIFICATION. LOCAL_MEAN_SOLAR_TIME	rotating solar system body.			
msn: <b>start_local_mean_solar_time</b>	start_local_mean_solar_time is the local mean solar time, as defined in the main PDS4 data dictionary.			
IDENTIFICATION. LOCAL_MEAN_SOLAR_TIME			ASCII_Short_String_Collapsed	
msn:start_local_true_solar_time	start_local_true_solar_time is the local true solar time, as defined in the main PDS4 data dictionary.			
IDENTIFICATION. LOCAL_TRUE_SOLAR_TIME	InSight Specific: The valid value is expressed in terms of a 24-hour clock, so the acceptable range is 00:00:00.000 to 23:59:59.999. See also LOCAL_TRUE_SOLAR_TIME_SOL for the sol number.		ASCII_Short_String_Collapsed	
msn:start_local_true_solar_time_sol	The start_local_true_solar_time_sol element specifies the number of solar days elapsed since a reference day (e.g.			
IDENTIFICATION. LOCAL_TRUE_SOLAR_TIME_SOL	the day on which a landing vehicle set down) for local true solar time (LTST). Days are measured in rotations of the planet in question from midnight to midnight. The reference day is '0', as Landing day is Sol 0. If before Landing day, then value will be less than or equal to '0' and can be negative.  Insight Specific:  The reference day is 0, as Landing day is Sol 0. If before Landing day, then value will be less than or equal to 0 and can be negative.		ASCII_Integer	
cart:lander_map_projection_name	The map_projection_name attribute provides the name of the map projection.	1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/lander map project		
SURFACE_PROJECTION_PARMS.  MAP_PROJECTION_TYPE		1) Cylindrical 2) Vertical 3) Perspective 4) Polar 5) Orthographic 6) Orthorectified 7) Cylindrical_Perspective	ASCII_Short_String_Collapsed	
cart:pixel_resolution_x  SURFACE_PROJECTION_PARMS. MAP_SCALE SURFACE_PROJECTION_PARMS. MAP_SCALE_UNIT	The pixel_resolution_x and pixel_resolution_y attributes indicate the image array pixel resolution (distance/pixel or degree/pixel) relative to the Cartesian (x,y) coordinate system as defined by the map projection. Due to varying properties across different map projections, actual surface distances for an individual pixel may be accurate only at specific location(s) within the image array (e.g. reference	1)/Product Observational/Observation Area/Discipline Area/Cartogra_System_Definition/Local/Map_Projection_Lander/Vertical/pixel_resolutions.  2)/Product Observational/Observation Area/Discipline Area/Cartogra_System Definition/Local/Map_Projection_Lander/Orthorectified/pixel	ution_x phy/Spatial Reference Information/Horizontal Coordinate	
	latitude or longitude, standard parallels, etc). For most PDS products, x and y resolution values are equal ('square' pixels). The inclusion of both x and y attributes allows for anticipated products where resolution may differ for each axis ('rectangular' pixels). NOTE: Definition of this PDS4 attribute differs from how 'resolution' was defined within PDS3.  InSight Specific:  Meters/pixel, corresponds to MAP_SCALE in VICAR/PDS 3		ASCII_Real  Units_of_Map_Scale	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
indicate the image degree/pixel) relat system as defined properties across of the state of the image of the image degree/pixel) relations as the image of the ima	The pixel_resolution_x and pixel_resolution_y attributes indicate the image array pixel resolution (distance/pixel or degree/pixel) relative to the Cartesian (x,y) coordinate system as defined by the map projection. Due to varying properties across different map projections, actual surface distances for an individual pixel may be accurate only at	1)/Product Observational/Observation Area/Discipline Area/Cartogra     System Definition/Local/Map Projection Lander/Vertical/pixel resol  2)/Product Observational/Observation Area/Discipline Area/Cartogra     System Definition/Local/Map Projection Lander/Orthorectified/pixel	ution_y phy/Spatial_Reference_Information/Horizontal_Coordinate	
	specific location(s) within the image array (e.g. reference latitude or longitude, standard parallels, etc). For most PDS products, x and y resolution values are equal ('square' pixels). The inclusion of both x and y attributes allows for anticipated products where resolution may differ for each axis ('rectangular' pixels). NOTE: Definition of this PDS4 attribute differs from how 'resolution' was defined within PDS3.  InSight Specific:  Meters/pixel, corresponds to MAP_SCALE in VICAR/PDS 3		ASCII_Real  Units_of_Map_Scale	
img:max_auto_exposure_iteration_count  OBSERVATION_REQUEST_PARMS.  MAX_AUTO_EXPOS_ITERATION_COUNT	The max_auto_exposure_iteration_count attribute specifies the maximum number of exposure iterations the instrument will perform in order to obtain the requested exposure.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Commanded Parameters/Exposure/Autoexposure/max to exposure iteration count  ASCII_Integer		
cart:maximum_elevation	The maximum_elevation attribute specifies the elevation (as defined by the coordinate system) of the first line of	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Cylindrical/maximum elevation		
SURFACE_PROJECTION_PARMS.  MAXIMUM_ELEVATION  SURFACE_PROJECTION_PARMS.  MAXIMUM_ELEVATIONUNIT	the image. For the Polar projection, specifies the highest elevation used, i.e. the elevation of the outermost circle of pixels. Applies to lander map projections Cylindrical, Polar, Sinusoidal, Perspective and Cylindrical-Perspective.		ASCII_Real  Units_of_Angle	
img_surface: <b>mesh_id</b>	The mesh_id attribute specifies which terrain mesh this			
IDENTIFICATION. <b>MESH_ID</b>	image should be automatically included in. This does not constrain which mesh(es) the image may be included in outside a pipeline environment.  InSight Specific:  Value is extracted from the image_id attributes value.  Meshes combine images with matching mesh_id,  sequence_id, and Epoch values. A mesh_id of 0 means do not include in a mesh. Values 1-9 mean to match within the same Sol only. Values 10-63 match globally across the entire mission. For non-raw products, any two characters, including non-numeric characters, may be used.		ASCII_Short_String_Collapsed	
cart:minimum_elevation	The minimum_elevation attribute specifies the elevation (as defined by the coordinate system) of the last line of the image for Cylindrical map projections. Applies to			
SURFACE_PROJECTION_PARMS.  MINIMUM_ELEVATION SURFACE_PROJECTION_PARMS.  MINIMUM_ELEVATIONUNIT	Image for Cylindrical map projections. Applies to Cylindrical, Perspective and Cylindrical-Perspective lander map projections.		ASCII_Real  Units_of_Angle	
missing_constant	The missing_constant attribute provides a value that indicates the original value was missing, such as due to a	1)/Product Observational/File Area Observational/Array 2D Image/Special Constants/missing constant		
IMAGE_DATA. <b>MISSING_CONSTANT</b>	gap in coverage.  InSight Specific:  The value should be 0.0 for most MUD, generated products.	2)/Product Observational/File Area Observational/Array 3D Image/Special Constants/missing constant		
	The value should be 0.0 for most MIPL-generated products.  No distinction is generally made between invalid and missing data.		ASCII_Short_String_Collapsed	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
msn:mission_phase_name	The mission_phase_name attribute provides the commonly recognized name for a mission phase.			
IDENTIFICATION. MISSION_PHASE_NAME	InSight Specific: For InSight the valid values are DEVELOPMENT, ATLO, CRUISE, SURFACE MISSION, and TEST.		ASCII_Short_String_Collapsed	
geom:Vector_Center	The Vector_Center describes the location of the entrance pupil of a camera.	1)/Product_Observational/Observation_Area/Discipline_Area/Geometr_ _Model/Vector_Center	ry/Geometry_Lander/Camera_Model_Parameters/CAHVORE	
GEOMETRIC_CAMERA_MODEL.  MODEL_COMPONENT_1  GEOMETRIC_CAMERA_MODEL.  MODEL_COMPONENT_UNIT		2)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Center	ry/Geometry Lander/Camera Model Parameters/CAHV M	
		3)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Center	y/Geometry Lander/Camera Model Parameters/CAHVOR	
		1) geom:x position 2) geom:y position 3) geom:z position 4) geom:Vector_Cartesian_Position_Base		
geom:Vector_Axis	The Vector_Axis is a unit vector that describes the axis of the camera, defined as the normal to the image plane.			
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_2				
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Axis		
		1) geom:x unit 2) geom:y unit 3) geom:z unit 4) geom:Vector_Cartesian_Unit		
geom:Vector_Horizontal	The Vector_Horizonal is a composite vector encoding three quantities: H' (a vector in the image plane perpendicular to the vertical columns), Hs (the distance between the lens	1)/Product Observational/Observation_Area/Discipline_Area/Geometr_ Model/Vector_Horizontal	ry/Geometry_Lander/Camera_Model_Parameters/CAHVORE	
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_3	the vertical columns), Hs (the distance between the lens center and image plane, measured in horizontal pixels), and Hc (the horizontal image coordinate directly under C when moving parallel to A). H' is often thought of as describing the orientation of rows in space, but is actually perpendicular to the columns.	2)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Horizontal	ry/Geometry Lander/Camera Model Parameters/CAHV M	
		3)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector Horizontal	ry/Geometry Lander/Camera Model Parameters/CAHVOR	
		1) geom:x pixel 2) geom:y pixel 3) geom:z pixel 4) geom:Vector_Cartesian_Pixel		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:Vector_Vertical	The Vector_Vertical is a composite vector encoding three quantities: V' (a vector in the image plane perpendicular to the horizontal rows), Vs (the distance between the lens	1)/Product_Observational/Observation_Area/Discipline_Area/Geometry/Geometry_Lander/Camera_Model_Parameters/CAHVORE_Model/Vector_Vertical	
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_4	center and image plane, measured in vertical pixels), and Vc (the vertical image coordinate directly under C when moving parallel to A). V' is often thought of as describing	2)/Product_Observational/Observation_Area/Discipline_Area/Geometrodel/Vector_Vertical	ry/Geometry_Lander/Camera_Model_Parameters/CAHV_M
	the orientation of columns in space, but is actually perpendicular to the rows.	3)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector Vertical	ry/ <u>Geometry Lander/Camera Model Parameters/CAHVOR</u>
		1) geom:x pixel 2) geom:y pixel 3) geom:z pixel 4) geom:Vector_Cartesian_Pixel	
geom:Vector_Optical	The Vector_Optical is a unit vector that describes the axis of symmetry for radial distortion in the camera.	1)/Product Observational/Observation Area/Discipline Area/Geometr Model/Vector_Optical	ry/Geometry Lander/Camera Model Parameters/CAHVORE
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_5		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR  Model/Vector Optical	
		1) geom:x unit 2) geom:y unit 3) geom:z unit 4) geom:Vector_Cartesian_Unit	
geom: <b>Radial_Terms</b>	Radial_Terms contains the coefficients of a polynomial function used to describe the radial distortion of the camera.	1)/Product Observational/Observation Area/Discipline Area/Geometre Model/Radial Terms	y/Geometry Lander/Camera Model Parameters/CAHVORE
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_6		2)/Product Observational/Observation Area/Discipline Area/Geometr Model/Radial Terms	ry/Geometry Lander/Camera Model Parameters/CAHVOR
		1) <u>geom:c0</u> 2) <u>geom:c1</u> 3) <u>geom:c2</u> 4) geom:Polynomial_Coefficients_3	
geom:Entrance_Terms	The Entrance_Terms contains the coefficients of a polynomial function used to model movement of the	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE Model/Entrance Terms	
GEOMETRIC_CAMERA_MODEL.  MODEL_COMPONENT_7	entrance pupil.	1) geom:c0 2) geom:c1 3) geom:c2 4) geom:Polynomial_Coefficients_3	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom: <b>x_position</b>	The x component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Center/x position		
GEOMETRIC_CAMERA_MODEL.  MODEL_COMPONENT_NAME		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry_Lander/Camera_Model Pararodel/Vector_Center/x_position		
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Center/x position		
		4)/Product Observational/Observation_Area/Discipline_Area/Geometrer_Corigin_Offset/x_position	y/Geometry_Lander/Coordinate_Space_Definition[*]/Vecto	
			ASCII_Real	
			Units_of_Length	
geom: <b>y_position</b>	The y component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Center/y position	y/Geometry Lander/Camera Model Parameters/CAHVORE	
GEOMETRIC_CAMERA_MODEL. MODEL_COMPONENT_NAME		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV odel/Vector Center/y position		
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Center/y position		
		4)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/Vectory Origin Offset/y position		
			ASCII_Real	
			Units_of_Length	
geom: <b>z_position</b>	The z component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Center/z position	y/Geometry_Lander/Camera_Model_Parameters/CAHVORE	
GEOMETRIC_CAMERA_MODEL.  MODEL_COMPONENT_NAME		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV Model/Vector Center/z position		
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Center/z position		
		4)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/Vector Offset/z position		
			ASCII_Real	
			Units_of_Length	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom: <b>qcos</b>	qcos is the scalar component of a quaternion. qcos = cos(theta/2), where theta is the angle of rotation.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/Quaton Model Transform/gcos		
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_QUATERNION		2)/Product Observational/Observation Area/Discipline Area/Geometrernion Plus Direction/qcos	y/Geometry Lander/Coordinate Space Definition[*]/Quat	
			ASCII_Real	
geom:qsin1	qsin1 is the first element of the vector component of a quaternion. qsin1 = x*sin(theta/2) where theta is the angle of rotation and (x,y,z) is the unit vector around which the	1)/Product Observational/Observation Area/Discipline Area/Geometron Model Transform/qsin1	y/Geometry Lander/Camera Model Parameters/Quaterni	
GEOMETRIC_CAMERA_MODEL. MODEL_TRANSFORM_QUATERNION	rotation occurs.	2)/Product Observational/Observation Area/Discipline Area/Geometrernion Plus Direction/qsin1	y/Geometry Lander/Coordinate Space Definition[*]/Quat	
			ASCII_Real	
geom:qsin2	qsin2 is the second element of the vector component of a quaternion. qsin2 = y*sin(theta/2) where theta is the angle of rotation and (x,y,z) is the unit vector around which the	1)/Product Observational/Observation Area/Discipline Area/Geometron Model Transform/qsin2	y/ <u>Geometry_Lander/Camera_Model_Parameters/Quaterni</u>	
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_QUATERNION	rotation occurs.	2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/Quaternion Plus Direction/qsin2		
			ASCII_Real	
geom:qsin3	qsin3 is the third element of the vector component of a quaternion. qsin3 = $z$ *sin(theta/2) where theta is the angle of rotation and $(x,y,z)$ is the unit vector around which the	1)/Product Observational/Observation Area/Discipline Area/Geometron Model Transform/qsin3	y/Geometry Lander/Camera Model Parameters/Quaterni	
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_QUATERNION	rotation occurs.	2)/Product Observational/Observation Area/Discipline Area/Geometrernion Plus Direction/gsin3	y/Geometry Lander/Coordinate Space Definition[*]/Quat	
			ASCII_Real	
geom: <b>x</b>	The x component of a Cartesian vector which has no units.	1)/Product Observational/Observation Area/Discipline Area/Geometr Model Transform/x	y/Geometry Lander/Camera Model Parameters/Vector	
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_VECTOR			ASCII_Real	
geom: <b>y</b>	The y component of a Cartesian vector which has no units.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/Vector Model Transform/y		
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_VECTOR			ASCII_Real	
geom:z	The z component of a Cartesian vector which has no units.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/Vector Model Transform/2		
GEOMETRIC_CAMERA_MODEL.  MODEL_TRANSFORM_VECTOR			ASCII_Real	
	The model_type attribute specifies an identifier for the type or kind of model. The value should be one of a well	1)/Product_Observational/Observation_Area/Discipline_Area/Geometr pe	y/ <u>Geometry_Lander/Camera_Model_Parameters/model_ty</u>	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:model_type  GEOMETRIC_CAMERA_MODEL. MODEL_TYPE	defined set, providing an application program with sufficient information to know how to handle the rest of the parameters within the model. This value will correlate directly with the specific camera model class that is a subclass of the Camera_Model_Parameters class.  InSight Specific: For InSight the camera model types are CAHV, CAHVOR, and CAHVORE.		ASCII_Short_String_Collapsed
img_surface: <b>mosaic_id</b>	The mosaic_id attribute specifies which mosaic this image should be automatically included in. This does not		
IDENTIFICATION. MOSAIC_ID	constrain which mosaic(s) the image may be included in outside a pipeline environment.  InSight Specific:  For InSight, value is extracted from the image_id value.  Mosaics combine images with matching mosaic_id, sequence_id, and Epoch values. A mosaic_id of 0 means do not include in a mesh. Values 1-9 mean to match within the same Sol only. Values 10-63 match globally across the entire mission. For non-raw products, any two characters, including non-numeric characters, may be used.		ASCII_Short_String_Collapsed
axes	The axes attribute provides a count of the axes.	1)/Product Observational/File Area Observational/Array 2D Image/axes	
SYSTEM. <b>NB</b>		2)/Product Observational/File Area Observational/Array 3D Image/axes	
		1) 3	ASCII_NonNegative_Integer
elements	The elements attribute provides the count of the number of elements along an array axis.	1)/Product Observational/File Area Observational/Array 2D Image/A	xis Array[*]/elements
SYSTEM. <b>NS</b> SYSTEM. <b>NL</b>		2)/Product_Observational/File_Area_Observational/Array_3D_Image/A	xis_Array[*]/elements
SYSTEM. <b>NB</b>			ASCII_NonNegative_Integer
img:analog_offset	The analog_offset attribute identifies the analog value that is subtracted from the signal prior to the analog/digital	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Detector/analog offset
INSTRUMENT_STATE_PARMS.  OFFSET_MODE_ID	conversion. InSight Specific: This value is the video offset, and has a range 0-4095.		ASCII_Integer
img:Onboard_Color_Matrix	The Onboard_Color_Matrix class represents a 3x3 matrix that is used onboard to perform color correction. It is done	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing/Onboard Color Matrix	
INSTRUMENT_STATE_PARMS.  ONBOARD_COLOR_MATRIX	after de-Bayering, as all three color bands are needed for each pixel. The first three elements are multiplied by the R,G,B (respectively) pixel values and summed to get the output Red pixel value. Similarly, the second three create the output Green, and the last three the output Blue. If the label is not present, no correction was performed.  InSight Specific:  It was decided before landing not to use this capability for InSight, because the effects of applying the matrix are not reversible on the ground. Thus this should be the identity matrix (1,0,0,0,1,0,0,0,1).	1) img:onboard R r 2) img:onboard R g 3) img:onboard R b 4) img:onboard G r 5) img:onboard G g 6) img:onboard G b 7) img:onboard B r 8) img:onboard B g 9) img:onboard B b	
		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Processing/Onboard Responsivity

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:Onboard_Responsivity  INSTRUMENT_STATE_PARMS.  ONBOARD_RESPONSIVITY	The Onboard_Responsivity class specifies factors that have been applied to the R, G, and B cells (respectively) of the Bayer pattern, before de-Bayering (demosaicking) takes place. The intent of these is to approximately balance the filters so the de-Bayering process is not skewed, and EDR/ILT products look reasonable before full radiometric or color correction is done on the ground. If these factors are not present, no correction was performed.  Insight Specific:  On InSight, this is used to boost the blue in order to compensate for markedly less responsivity in the blue sensors, providing a better approximation of the color of the scene in the EDR/ILT.	1) ima:responsivity factor r 2) ima:responsivity factor q 3) ima:responsivity factor b	
img:responsivity_factor_r	Specifies the factor that has been applied to the R cell of the Bayer pattern, before de-Bayering (demosaicking) takes place.	1)/Product Observational/Observation Area/Discipline Area/Imaging/ or r	Color Processing/Onboard Responsivity/responsivity fact
INSTRUMENT_STATE_PARMS.  ONBOARD_RESPONSIVITY  InSight Specific: On InSight, this is use: compensate for mark sensors, providing a b	· ·		ASCII_Real
img:responsivity_factor_g	Specifies the factor that has been applied to the G cell of the Bayer pattern, before de-Bayering (demosaicking)	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Color_Processing/Onboard_Responsivity/responsivity_fact or_g	
INSTRUMENT_STATE_PARMS.  ONBOARD_RESPONSIVITY			ASCII_Real
img:responsivity_factor_b	Specifies the factor that has been applied to the B cell of the Bayer pattern, before de-Bayering (demosaicking) takes place.	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Color_Processing/Onboard_Responsivity/responsivity_fact or_b	
INSTRUMENT_STATE_PARMS.  ONBOARD_RESPONSIVITY	InSight Specific:  On InSight, this is used to boost the blue in order to compensate for markedly less responsivity in the blue sensors, providing a better approximation of the color of the scene in the EDR/ILT.		ASCII_Real
geom:Vector_Origin_Offset	The Vector_Origin_Offset class contains attributes that specify the offset from the reference coordinate system's origin to the origin of the coordinate system. It is the	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/Vector_Origin_Offset	
LANDER_COORDINATE_SYSTEM. ORIGIN_OFFSET_VECTOR	location of the current system's origin as measured in the reference system.	1) geom:x position 2) geom:y position 3) geom:z position 4) geom:Vector_Cartesian_Position_Base	
	Quaternion_Plus_Direction provides the four elements of a quaternion and its direction of rotation. The two end point	1)/Product Observational/Observation Area/Discipline Area/Geometric ernion Plus Direction	y/Geometry_Lander/Coordinate_Space_Definition[*]/Quat

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:Quaternion_Plus_Direction  LANDER_COORDINATE_SYSTEM.  ORIGIN_ROTATION_QUATERNION	frames must be identified in the enclosing class. See the definition of Quaternion_Base for more details on the quaternion classes in this dictionary.  InSight Specific:  Note that quaternions have different component order conventions between flight and ground software. They are received in the order (v1, v2, v3, s). However, the ground order convention is is (s, v1, v2, v3), and all values are converted to the ground order before being stored in the label. For InSight, the value for ORIGIN_ROTATION_QUATERNION that defines a coordinate frame like Lander frame is computed with respect to only the orientations of the frame's axes regardless of whether POSITIVE_ELEVATION_DIRECTION is declared to be UP or DOWN.	1) geom:qcos 2) geom:qsin1 3) geom:rotation direction 4) geom:qsin2 5) geom:qsin3	
img:height_pixels	The height_pixels attribute provides the vertical dimension, in pixels.	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Downsampling/Pixel_Averaging_Dimensions/height_pixels	
INSTRUMENT_STATE_PARMS.	InSight Specific: InSight does not support downsampling, so this value is		ASCII_NonNegative_Integer
PIXEL_AVERAGING_HEIGHT	always 1.		Units_of_Misc
img:width_pixels	The width_pixels attribute provides the horizontal dimension, in pixels.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Downsampling/Pixel Averaging Dimensions/width pixels	
INSTRUMENT_STATE_PARMS. PIXEL_AVERAGING_WIDTH	InSight Specific: InSight does not support downsampling, so this value is		ASCII_NonNegative_Integer
PIXEL_AVERAGING_WIDTH	always 1.		Units_of_Misc
msn: <b>start_sol_number</b>	The start_sol_number is the number of the Mars day on which an observation began. Landing day is Sol 0.		
IDENTIFICATION. PLANET_DAY_NUMBER	222		ASCII_Integer
geom:positive_azimuth_direction	The positive_azimuth_direction attribute specifies the direction in which azimuth is measured in positive degrees for an observer on the surface of a body. The azimuth is	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/ ve_azimuth_direction	
LANDER_COORDINATE_SYSTEM.  POSITIVE_AZIMUTH_DIRECTION	measured with respect to the elevation reference plane. A value of 'clockwise' indicates that azimuth is measured positively clockwise, and 'counterclockwise' indicates that azimuth increases positively counter-clockwise.  InSight Specific:  For operational coordinate frames, which follow the Mars Pathfinder convention, increasing azimuth moves in a clockwise (CLOCKWISE) direction as viewed from above.	1) Clockwise 2) Counterclockwise 3) CW 4) CCW	ASCII_Short_String_Collapsed
	The positive_elevation_direction attribute provides the direction in which elevation is measured in positive	1)/Product Observational/Observation Area/Discipline Area/Geometrve elevation direction	y/Geometry Lander/Coordinate Space Definition[*]/positi

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
geom:positive_elevation_direction  LANDER_COORDINATE_SYSTEM.  POSITIVE_ELEVATION_DIRECTION	degrees for an observer on the surface of a body. The elevation is measured with respect to the azimuthal reference plane. A value of UP or ZENITH indicates that elevation is measured positively upwards, i.e., the zenith point would be at +90 degrees and the nadir point at -90 degrees. DOWN or NADIR indicates that the elevation is measured positively downwards; the zenith point would be at -90 degrees and the nadir point at +90 degrees.  InSight Specific:  For operational coordinate frames, which follow the Mars Pathfinder convention, the positive elevation direction is UP.	1) Up 2) Zenith 3) Down 4) Nadir	ASCII_Short_String_Collapsed
proc:process_owner_institution_name	The pprocess_owner_institution_name attribute specifies the name of the institution that owns the software	1)/Product Observational/Observation Area/Discipline Area/Processin	ng Information/Process/process owner institution name
IDENTIFICATION. PRODUCER_INSTITUTION_NAME	process.		ASCII_Short_String_Collapsed
msn_surface:product_completion_status	The product_completion_status attribute indicates whether or not a product is complete or is in one of a		
TELEMETRY. PRODUCT_COMPLETION_STATUS	number of not a product is complete or is in one of a number of incomplete states. Sample values might indicate that all portions of the product have been downlinked and received correctly, that all portions have not yet been received, or that the product contains transmission errors. The specific values are mission-dependent.	1) PARTIAL 2) COMPLETE	ASCII_Short_String_Collapsed
creation_date_time	The creation_date_time attribute provides a date and time when the object was created.	1)/Product Collection/File Area Inventory/File/creation date time	
IDENTIFICATION. PRODUCT_CREATION_TIME	InSight Specific: This represents the Earth time when the product was created, not the time the spacecraft acquired the data.	2)/Product XML Schema/File Area XML Schema[*]/File/creation_date_time	
		3)/Product Observational/File Area Observational/File/creation_date	time
		4)/Product Browse/File Area Browse/File/creation_date_time	
			ASCII_Date_Time_YMD
logical_identifier	A logical identifier identifies the set of all versions of an object. It is an object identifier without a version.	1)/Product Collection/Identification Area/logical identifier	
IDENTIFICATION. <b>PRODUCT_ID</b>		2)/Product_XML_Schema/Identification_Area/logical_identifier	
		3)/Product_File_Text/Identification_Area/logical_identifier	
		4)/Product Document/Identification Area/logical identifier	
		5)/Product Observational/Identification Area/logical identifier	
		6)/Product Browse/Identification Area/logical identifier	
			ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
file_name	The file_name attribute provides the name of a file.  InSight Specific:	1)/Product Collection/File Area Inventory/File/file name		
IDENTIFICATION. <b>PRODUCT_ID</b>	For InSight this contains the VICAR PRODUCT_ID, which is the filename minus the extension.	2)/Product Observational/File Area Observational Supplemental[*]/F	ile/file_name	
		3)/Product XML Schema/File Area XML Schema[*]/File/file name		
		4)/Product File Text/File Area Text/File/file name		
		5)/Product_Document/Document_Edition/Document_File/f	ile_name	
		6)/Product Observational/File Area Observational/File/file name		
		7)/Product Observational/File Area Observational Supplemental/File	file_name	
		8)/Product_Browse/File_Area_Browse/File/file_name		
			ASCII_Short_String_Collapsed	
alternate_id	The alternate_id attribute provides an additional identifier supplied by the data provider.	1)/Product Observational/Identification Area/Alias List/Alias/alternat	e id	
IDENTIFICATION. PRODUCT_ID	InSight Specific:		ASCII_Short_String_Collapsed	
local_identifier_reference	The local_identifier_reference attribute provides the value of the local_identifier of the entity described by the referencing class. Note that a local_identifier attribute,	1)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Space eference/Local Internal Reference/local identifier reference  2)/Product Observational/Observation Area/Discipline Area/Cartography/Local Internal Reference/local identifier reference		
IDENTIFICATION. PRODUCT_ID	with the same value as this local_identifier_reference, must be present within the label.			
		3)/Product_Observational/Observation_Area/Discipline_Area/Display_0	Settings/Local Internal Reference/local identifier reference	
		4)/Product Observational/Observation Area/Discipline Area/Geometr te_Space_Reference/Local_Internal_Reference/local_identifier_referen		
		5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[2]/ dinate Space Reference/Local Internal Reference/local identifier reference		
	6)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived ce Reference/Local Internal Reference/local identifier reference		y/Geometry Lander/Derived Geometry[1]/Coordinate Spa	
		7)/Product Observational/Observation Area/Discipline Area/Imaging/Local Internal Reference/local identifier reference  8)/Product Observational/Observation Area/Discipline Area/Processing Information/Local Internal Reference/local identifier reference  eference		
			ASCII_Local_Identifier_Reference	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
cart:projection_azimuth	The projection_azimuth attribute specifies the azimuth of the horizontal center of projection for the Perspective	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Perspective/projection azimuth		
SURFACE_PROJECTION_PARMS. PROJECTION_AZIMUTH	lander map projection (loosely, where the camera model is pointing).		ASCII_Real	
			Units_of_Angle	
cart:projection_elevation	The projection_elevation attribute specifies the elevation of the vertical center of projection (loosely, where the camera is pointing). For Perspective lander map projection,	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coord System Definition/Local/Map Projection Lander/Perspective/projection elevation		
SURFACE_PROJECTION_PARMS. PROJECTION_ELEVATION	this applies to the single output camera model; for Cylindrical-Perspective it applies to each columns output camera model, before the rotation specified by	2)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Cylindrical Perspect		
	Vector_Projection_Z_Axis.		ASCII_Real	
			Units_of_Angle	
cart:projection_elevation_line	The projection_elevation_line attribute specifies the image line which corresponds to the projection_elevation attribute for each column of the Cylindrical-Perspective	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal System Definition/Local/Map Projection Lander/Cylindrical Perspective/projection_elevation_line		
SURFACE_PROJECTION_PARMS. PROJECTION_ELEVATION_LINE	projection, before the rotation specified by Vector_Projection_Z_Axis.		ASCII_Real	
cart:x_position	The x component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Cylindrical/Vector I	phy/Spatial Reference Information/Horizontal Coordinate Projection Origin/x position	
SURFACE_PROJECTION_PARMS. PROJECTION_ORIGIN_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Cartogra _System Definition/Local/Surface Model Parameters/Surface Model		
			ASCII_Real	
			Units_of_Length	
cart:y_position	The y component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Cylindrical/Vector (		
SURFACE_PROJECTION_PARMS. PROJECTION_ORIGIN_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Ho System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Ground Location		
			ASCII_Real	
			Units_of_Length	
cart:z_position	The z component of a Cartesian position vector.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Cylindrical/Vector Projection Origin/z position		
SURFACE_PROJECTION_PARMS. PROJECTION_ORIGIN_VECTOR		2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Ground Location/z position		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
			ASCII_Real
			Units_of_Length
cart:Vector_Projection_Origin  SURFACE_PROJECTION_PARMS. PROJECTION_ORIGIN_VECTOR	The Vector_Projection_Origin class specifies the location of the origin of the projection. For Polar and Cylindrical projections, this is the XYZ point from which all the azimuth/elevation rays emanate. For the Cylindrical-Perspective projection, this defines the center of the circle around which the synthetic camera orbits. For Orthographic, Orthorectified, and Vertical projections, this optional keyword specifies the point on the projection plane that serves as the origin of the projection (i.e. all points on a line through this point in the direction of PROJECTION_Z_AXIS_VECTOR will be ocated at X=Y=0 in the projection). If not present, (0,0,0) should be assumed. This translation is generally not necessary and not often used; the (X Y)_AXIS_MINIMUM and (X Y)_AXIS_MAXIMUM fields allow the mosaic to be located arbitrarily in the projection plane.	1)/Product Observational/Observation Area/Discipline Area/Cartogral System Definition/Local/Map Projection Lander/Cylindrical/Vector F  1) geom:x position 2) geom:y position 3) geom:z position 4) cart:Vector_Cartesian_Position_Base	ohy/Spatial Reference Information/Horizontal Coordinate Projection Origin
value_offset  DERIVED_IMAGE_PARMS. RADIANCE_OFFSET	The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: Ov = (Sv * scaling_factor) + value_offset. The	1)/Product Observational/File Area Observational/Array 2D Image/Element Array/value offset  2)/Product Observational/File Area Observational/Array 3D Image/Element Array/value offset	
	default value is 0.		ASCII_Real
unit  DERIVED_IMAGE_PARMS.  RADIANCE_OFFSETUNIT	The unit attribute provides the unit of measurement.  InSight Specific:  This defines the unit of measurement for the data (image pixels) themselves.	1)/Product Observational/File Area Observational/Array 2D Image/E 2)/Product Observational/File Area Observational/Array 3D Image/E	<del></del>
DERIVED_IMAGE_PARMS. RADIANCE_SCALING_FACTOR_UNIT			UTF8_Short_String_Collapsed
scaling_factor	The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original	1)/Product Observational/File Area Observational/Array 2D Image/E	lement Array/scaling factor
DERIVED_IMAGE_PARMS.  RADIANCE_SCALING_FACTOR	value. The observed value (Ov) is calculated from the stored value (Sv) thus: Ov = (Sv * scaling_factor) +	2)/Product Observational/File Area Observational/Array 3D Image/Element Array/scaling factor	
	value_offset. The default value is 1.		ASCII_Real
img:radiometric_type	The radiometric_type defines the specific type of radiance measurement. Possible values include "Radiance",	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Radiometric Correction/radiometric type
DERIVED_IMAGE_PARMS. RADIOMETRIC_CORRECTION_TYPE	"Spectral Radiance", "Scaled Spectral Radiance". Note: There are many more possible values, and this definition can be updated to include more examples over time. InSight Specific: The InSight pipeline uses 'MIPLRAD' (see description in main body of SIS).		ASCII_Short_String_Collapsed
img_surface:Vector_Range_Origin  DERIVED_IMAGE_PARMS. RANGE_ORIGIN_VECTOR	The Vector_Range_Origin class specifies the 3-D space from which the Range values are measured in a Range RDR. This will normally be the same as the C point of the camera. It is expressed in the coordinate system specified by the Coordinate_Space_Reference class.	1) img surface:x position 2) img surface:y position 3) img surface:z position	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img_surface: <b>x_position</b>	The x component of a Cartesian position vector.		
DERIVED_IMAGE_PARMS.  RANGE_ORIGIN_VECTOR			ASCII_Real
NAIVOL_ONION_VECTOR			Units_of_Length
img_surface: <b>y_position</b>	The y component of a Cartesian position vector.		
DERIVED_IMAGE_PARMS.			ASCII_Real
RANGE_ORIGIN_VECTOR			Units_of_Length
img_surface: <b>z_position</b>	The z component of a Cartesian position vector.		
DERIVED_IMAGE_PARMS.			ASCII_Real
RANGE_ORIGIN_VECTOR			Units_of_Length
msn_surface:received_packets	The received_packets attribute provides the total number		
TELEMETRY. RECEIVED_PACKETS	of telemetry packets actually used to construct this data product. cf. expected_packets.		ASCII_NonNegative_Integer

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Unit</i> s	
geom:index_value_number  *. REFERENCE_COORD_SYSTEM_INDEX *_COORDINATE_SYSTEM. COORDINATE_SYSTEM_INDEX IDENTIFICATION. ROVER_MOTION_COUNTER *_ARTICULATION_STATE. ARTICULATION_DEVICE_TEMP_COUNT	InSight-Specific Information  The index_value_number attribute provides the value with no applicable units as named by the associated index_id or index_name.  InSight Specific: For InSight, the Device_Temperature instance contains raw temperature counts. The rest of the instances contain coordinate space indices.	Children (class)  Units  1)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Space Indexed/Coordinate Space Indexed/Product Parameters/Coordinate Space Indexed/Coordinate Space Indexed/Product Parameters/Coordinate Space Index		
		1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	/Sampling/sample_bits	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
img:sample_bits  IMAGE_DATA. SAMPLE_BIT_MASK	The sample_bits attribute specifies the logical or active number of bits in the data, which is distinct from the physical number of bits (for example, encoding 12-bit data within 16-bit words). These logical bits are stored in the low order (least significant) bits, with unused bits filled with 0 (or 1 for negative integers to preserve a two's complement representation). This is distinct from the valid data range (specified by valid_minimum and valid_maximum in Special_Constants class) because all values, including missing/invalid flag values, must fit within the sample_bits. The intent is that the data should be able to be sent through a communication channel that passes only sample_bits with no loss in fidelity.  InSight Specific:  In VICAR this quantity is maintained as a bit mask; this is converted to a number of bits for PDS4.		ASCII_Short_String_Collapsed
img:processing_venue	The processing_venue attribute specifies where the processing described by the parent class was performed.	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	Radiometric_Correction/processing_venue
INSTRUMENT_STATE_PARMS. SAMPLE_BIT_METHOD		2)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Filter Array/processing venue
		3)/Product Observational/Observation Area/Discipline Area/Imaging/Sampling/Companding/processing venue	
		4)/Product Observational/Observation Area/Discipline Area/Imaging/Shutter Subtraction/processing venue	
		5)/Product Observational/Observation Area/Discipline Area/Imaging/Commanded Parameters/Shutter Subtraction/processing venue	
		1) Onboard Hardware 2) Onboard Software 3) Onboard Both 4) Onboard 5) Ground 6) Ground Refined 7) None	ASCII_Short_String_Collapsed
img:active_flag	The active_flag attribute indicates whether or not the data processing described by the parent class is active. In	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Radiometric Correction/active flag
OBSERVATION_REQUEST_PARMS. SHUTTER_CORRECTION_MODE	general, the presence of the parent class is active. In general, the presence of the parent class implies it is active and thus active_flag is optional. The primary purpose for active flag is to either explicitly indicate a correction is not	2)/Product Observational/Observation Area/Discipline Area/Imaging/Shutter Subtraction/active flag	
	active (for example, if it normally is but was explicitly turned off), or to be able to provide parameters for	3)/Product Observational/Observation Area/Discipline Area/Imaging/Commanded Parameters/Shutter Subtraction/active fl	
	historical reasons that may no longer be relevant to a current correction.		ASCII_Boolean
img:shutter_subtraction_mode	The shutter_subtraction_mode specifies whether shutter subtraction will be performed, or if it is dependent on the	1)/Product Observational/Observation Area/Discipline Area/Imaging/Shutter Subtraction/shutter subtraction mode	
OBSERVATION_REQUEST_PARMS. SHUTTER_CORRECTION_MODE	exposure_duration_threshold_count.	2)/Product Observational/Observation Area/Discipline Area/Imaging/ traction mode	Commanded Parameters/Shutter Subtraction/shutter sub
		1) True 2) Conditional	ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom: <b>solar_azimuth</b>	The solar_azimuth attribute specifies one of two angular measurements indicating the direction to the Sun as	1)/Product_Observational/Observation_Area/Discipline_Area/Geometry/Geometry_Lander/Derived_Geometry[*]/solar_azimuth	
SITE_DERIVED_GEOMETRY_PARMS. SOLAR_AZIMUTH SITE_DERIVED_GEOMETRY_PARMS. SOLAR_AZIMUTHUNIT	measured from a specific point on the surface of a planet (eg., from a lander or rover). The positive direction of azimuth is set by the positive_azimuth_direction attribute in the reference coordinate space. The azimuth is measured in the clockwise or counterclockwise direction (as viewed from above) with the meridian passing through the positive spin axis of the planet (i.e., the north pole) defining the zero reference.  InSight Specific:  Computed using SPICE.		ASCII_Real  Units_of_Angle
geom:solar_elevation	The solar_elevation attribute specifies one of two angular measurements indicating the direction to the Sun as	1)/Product Observational/Observation Area/Discipline Area/Geometr	y/Geometry_Lander/Derived_Geometry[*]/solar_elevation
SITE_DERIVED_GEOMETRY_PARMS.  SOLAR_ELEVATION	measured from a specific point on the surface of a planet (eg., from a lander or rover). The positive direction of the elevation is set by the positive_elevation_direction		ASCII_Real
SITE_DERIVED_GEOMETRY_PARMS.  SOLAR_ELEVATIONUNIT	attribute in the reference coordinate space. The elevation is measured from the plane which is normal to the line passing between the surface point and the planet's center of mass, and that intersects the surface point.  InSight Specific:  Computed using SPICE.		Units_of_Angle
solar_longitude	The solar_longitude attribute provides the angle between the body-Sun line at the time of interest and the body-Sun	1)/Product Observational/Observation Area/Time Coordinates/solar longitude	
IDENTIFICATION. SOLAR_LONGITUDE	line at its vernal equinox.  InSight Specific:		ASCII_Real
	This provides a measure of season on a target body, with values of 0 to 90 degrees representing northern spring, 90 to 180 degrees representing northern summer, 180 to 270 degrees representing northern autumn and 270 to 360 degrees representing northern winter. Note that this duplicates the solar_longitude in the pds: dictionary.		Units_of_Angle
msn: <b>solar_longitude</b>	solar_longitude is the solar longitude, as defined in the		
IDENTIFICATION. SOLAR_LONGITUDE	main PDS4 data dictionary. InSight Specific: This provides a measure of season on a target body, with values of 0 to 90 degrees representing northern spring, 90 to 180 degrees representing northern summer, 180 to 270 degrees representing northern autumn and 270 to 360 degrees representing northern winter. Note that this duplicates the solar_longitude in the pds: dictionary.		ASCII_Real  Units_of_Angle
	The solution_id attribute specifies the unique identifier for the solution set to which the values in the group belong.	1)/Product Observational/Observation Area/Discipline Area/Geometr dinate Space Present/Coordinate Space Indexed/solution id	y/Geometry_Lander/Coordinate_Space_Definition[*]/Coor

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:solution_id  *_COORDINATE_SYSTEM. SOLUTION_ID	For certain kinds of information, such as pointing correction (pointing models) and rover localization (coordinate system definitions), the "true" value is unknown and only estimates of the true value exist. Thus, more than one set of estimates may exist simultaneously, each valid for its intended purpose. Each of these sets is called a "solution" to the unknown true value. The solution_id attribute is used to identify which solution is being expressed by the containing group. No specific naming convention is defined here, however it is recommended that projects adopt one. The intent is to be able to identify who created the solution, and why. Possible components of the naming convention include user, institution, purpose, request ID, version, program, date/time.  InSight Specific:  Must be globally unique across all coordinate system instances, i.e. it cannot be reused to define the same coordinate system instance differently. Different coordinate system instance (for example, different values of the RMC index) may share the same SOLUTION_ID. See also REFERENCE_COORD_SYSTEM_NAME and  REFERENCE_COORD_SYSTEM_SOLN_ID. The SOLUTION_ID should be the same identifier used in the PLACES rover localization database. The special name 'telemetry' is used for values telemetered from the rover. If SOLUTION_ID is absent, 'telemetry' should be assumed.		ASCII_Short_String_Collapsed
lidvid_reference  IDENTIFICATION. SOURCE_PRODUCT_ID	The lidvid_reference attribute provides the logical_identifier plus version_id, which uniquely identifies a product.  InSight Specific:  References of type 'data_to_raw_product' point at the raw products (aka EDRs) that ultimately provided the data used to make this product.	2)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product[*]/Intal Reference/lidvid reference	
msn:spacecraft_clock_partition	The spacecraft_clock_partition provides the clock partition active for the spacecraft_clock attribute.  InSight Specific:		ASCII Integer
IDENTIFICATION.  SPACECRAFT_CLOCK_CNT_PARTITION	Always 1 for InSight.		ASCII_Integer
msn: <b>spacecraft_clock_start</b>	The spacecraft_clock_start is the value of the spacecraft clock at the beginning of the observation.		
IDENTIFICATION. SPACECRAFT_CLOCK_START_COUNT			ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
msn: <b>spacecraft_clock_stop</b>	The spacecraft_clock_stop is the value of the spacecraft clock at the end of the observation. spacecraft_clock_stop		
IDENTIFICATION. SPACECRAFT_CLOCK_STOP_COUNT	should only be used if there's also a spacecraft_clock_start value.		ASCII_Short_String_Collapsed
geom: <b>spice_kernel_file_name</b>	The spice_kernel_file_name attribute provides the file name of a SPICE kernel file used to process the data or to produce geometric quantities given in the label.	1)/Product Observational/Observation Area/Discipline Area/Geometr rnel_file_name	ry/SPICE Kernel Files/SPICE Kernel Identification/spice ke
TELEMETRY. <b>SPICE_FILE_NAME</b>	produce geometric quantities given in the label.		ASCII_File_Name
cart:start_azimuth  SURFACE_PROJECTION_PARMS. START_AZIMUTH	The start_azimuth specifies the angular distance from a fixed reference position at which an image or observation starts. Azimuth is measured in a spherical coordinate system, in a plane normal to the principal axis. Azimuth values increase according to the right hand rule relative to the positive direction of the principal axis of the spherical	1)/Product Observational/Observation Area/Discipline Area/Cartogra     System Definition/Local/Map Projection Lander/Cylindrical/start azi  2)/Product Observational/Observation Area/Discipline Area/Cartogra     System Definition/Local/Map Projection Lander/Cylindrical Perspect	phy/Spatial Reference Information/Horizontal Coordinate
	coordinate system. For lander map projections, this attribute specifies the azimuth of the left edge of the output map. Applies to Cylindrical and Cylindrical-		ASCII_Real
	Perspective lander map projections only.		Units_of_Angle
geom: <b>start_azimuth</b>	The start_azimuth attribute specifies the angular distance from a fixed reference position at which an image or	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived Geometry/start azimuth	
*_DERIVED_GEOMETRY_PARMS. START_AZIMUTH	observation starts. Azimuth is measured in a spherical coordinate system, in a plane normal to the principal axis. Azimuth values increase according to the right hand rule relative to the positive direction of the principal axis of the spherical coordinate system. When applied to a site or surface projection coordinate space, specifies the azimuth of the left edge of the output map. Applies to Cylindrical and Cylindrical-Perspective projections only.		ASCII_Real  Units_of_Angle
start_date_time	The start_date_time attribute provides the date and time appropriate to the beginning of the product being labeled.	1)/Product Collection/Context Area/Time Coordinates/start date time	i <u>e</u>
IDENTIFICATION. START_TIME	InSight Specific: The time period of interest is returned from SPICE	2)/Product_Observational/Observation_Area/Time_Coordinates/start_date_time	
	subroutines and is based on the beginning of data acquisition.		ASCII_Date_Time_YMD_UTC
img_surface: <b>stereo_match_id</b>	The stereo_match_id attribute specifies which other image this image matches with for stereo processing. If used for a		
IDENTIFICATION. STEREO_MATCH_ID	mission, the two images making up a stereo pair should share the same stereo_match_id value.  Insight Specific:  The stereo_match_id is derived from the image_id (see SIS Appendix A). Numeric values indicate commanded stereo pairs; alpha values indicate ground-assigned stereo pairs. In order for an image pair to be matched for stereo, the sequence_id, mesh_id, and sol also need to match, in addition to stereo_match_id.		ASCII_Short_String_Collapsed
cart:stop_azimuth  SURFACE PROJECTION PARMS. STOP AZIMUTH	The stop_azimuth attribute pecifies the angular distance from a fixed reference position at which an image or observation stops. Azimuth is measured to the existing of the stops of the st	System Definition/Local/Map Projection Lander/Cylindrical/stop azimuth	
	coordinate system, in a plane normal to the principal axis.  Azimuth values increase according to the right hand rule	2)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Cylindrical Perspect	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	relative to the positive direction of the principal axis of the spherical coordinate system. For lander map projections,		ASCII_Real
	this attribute specifies the azimuth of the right edge of the output map. Applies to Cylindrical and Cylindrical-Perspective lander map projections only.		Units_of_Angle
geom: <b>stop_azimuth</b>	The stop_azimuth attribute specifies the angular distance from a fixed reference position at which an image or	1)/Product Observational/Observation Area/Discipline Area/Geometre	y/Geometry Lander/Derived Geometry/stop azimuth
*_DERIVED_GEOMETRY_PARMS. STOP_AZIMUTH	observation stops. Azimuth is measured in a spherical coordinate system, in a plane normal to the principal axis.  Azimuth values increase according to the right hand rule		ASCII_Real
	relative to the positive direction of the principal axis of the spherical coordinate system. When applied to a site or surface projection coordinate space, specifies the azimuth of the right edge of the output map. Applies to Cylindrical and Cylindrical-Perspective projections only.		Units_of_Angle
stop_date_time	The stop_date_time attribute provides the date and time appropriate to the end of the product being labeled.	1)/Product Collection/Context Area/Time Coordinates/stop date time	<u>e</u>
IDENTIFICATION. STOP_TIME	InSight Specific: The time period of interest is returned from SPICE	2)/Product Observational/Observation Area/Time Coordinates/stop_date_time	
	suburoutines and is based on the end of data acquisition.		ASCII_Date_Time_YMD_UTC
cart:Vector_Surface_Ground_Location	The Vector_Surface_Ground_Location class specifies any point on the surface. This point is measured in the coordinates specified by the Coordinate Space reference	System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Ground Location	
SURFACE_MODEL_PARMS. SURFACE_GROUND_LOCATION	_MODEL_PARMS. in the Surface Model Parameters class.	1) geom:x position 2) geom:x position 3) geom:z position 4) cart:Vector_Cartesian_Position_Base	
cart:surface_model_type	Specifies the type of surface used for the reprojection performed during the mosaicking process. Valid values:	1)/Product_Observational/Observation_Area/Discipline_Area/Cartogra_ System_Definition/Local/Surface_Model_Parameters/surface_model	
SURFACE_MODEL_PARMS. SURFACE_MODEL_TYPE	Planar - refers to a flat planar model; Spherical refers to a spherical model where the camera is at the center of the sphere.	1) Spherical 2) Planar	ASCII_Short_String_Collapsed
cart:Vector_Surface_Normal	The Vector_Surface_Normal class specifies a vector normal to the planar surface. This vector is measured in the	1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Surface Model Parameters/Surface Model	
SURFACE_MODEL_PARMS. SURFACE_NORMAL_VECTOR	coordinates specified by the Coordinate_Space reference in the Surface_Model_Parameters class.	1) cart:x unit 2) cart:y unit 3) cart:z unit 4) cart:Vector_Cartesian_Unit_Base	
cart: <b>x_unit</b>	The x component of a unit vector.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Normal/x unit	
SURFACE_MODEL_PARMS. SURFACE_NORMAL_VECTOR			ASCII_Real
cart: <b>y_unit</b>	The y component of a unit vector.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Normal/y unit	
SURFACE_MODEL_PARMS. SURFACE_NORMAL_VECTOR			ASCII_Real

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
cart: <b>z_unit</b>	The z component of a unit vector.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinat System Definition/Local/Surface Model Parameters/Surface Model Planar/Vector Surface Normal/z unit		
SURFACE_MODEL_PARMS. SURFACE_NORMAL_VECTOR			ASCII_Real	
img_surface:Placement_Target_Instrument	Indicates the instrument that is referred to by the product. This is not the same as the instrument that acquired the			
DERIVED_IMAGE_PARMS. TARGET_INSTRUMENT	product. For example, on InSight instrument placement products, it defines which instrument is being placed.	1) <u>name</u> 2) <u>Internal_Reference</u>		
msn_surface: <b>provider_id</b>	The provider_id attribute identifies the organization or subsystem that supplied the telemetry data product to the			
TELEMETRY. TELEMETRY_PROVIDER_ID	producer of the raw (EDR) PDS data product. This is typically (but not always) the organization responsible for reassembling packetized data into a single product. These may vary by mission so the permissible values should be set by the mission dictionaries.  InSight Specific: For InSight the subsystem is TTACS		ASCII_Short_String_Collapsed	
msn_surface: <b>telemetry_source_name</b>	The telemetry_source_name specifies the name source of the telemetry data described in the parent class.			
TELEMETRY. TELEMETRY_SOURCE_NAME	InSight Specific: For InSight this is either 'TDS' for the telemetry server, or the name of the SFDU file or CCSDS packet directory used as input to the EDR generator.		ASCII_Short_String_Collapsed	
msn_surface: <b>telemetry_source_sclk_start</b>	The telemetry_source_sclk_start attribute specifies the value of the spacecraft clock (in seconds) at the creation			
TELEMETRY. TELEMETRY_SOURCE_SCLK_START	time of the source product from which this product was derived.  InSight Specific:  This is the time in the CCSDS header. Used to find all the matching packets for one product.		ASCII_Short_String_Collapsed	
msn_surface:telemetry_source_start_time	The telemetry_source_start_time specifies the creation time of the source product from which this product was			
TELEMETRY. TELEMETRY_SOURCE_START_TIME	derived. It is the same as the telemetry_source_sclk_start converted to Spacecraft Event Time (SCET).		ASCII_Date_Time_YMD_UTC	
msn_surface: <b>transport_protocol</b>	The transport_protocol attribute specifies the protocol used in the creation of the telemetry data products by the			
TELEMETRY. TELEMETRY_SOURCE_TYPE	subsystem which generates the telemetry stream.  InSight Specific: For InSight this is always SFDU.	1) SFDU 2) Data Product	ASCII_Short_String_Collapsed	
proc: <b>program_user</b>	The program_user attribute specifies the username of the person responsible for running the software prgoram.	1)/Product Observational/Observation Area/Discipline Area/Processing Information/Process/Software/Software Program[*]/program_user  2)/Product Observational/Observation Area/Discipline Area/Processing Information/Process/Software/Software Program/program_user		
*. USER				
			ASCII_Short_String_Collapsed	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>	
cart:x_axis_maximum  SURFACE_PROJECTION_PARMS. X_AXIS_MAXIMUM SURFACE_PROJECTION_PARMS.	The x_axis_maximum attribute specifies the value of the X coordinate (measured in the projection frame) of a Vertical, Orthographic or Orthorectified lander map projection at the top of the image. Note that +X is at the top of the image and +Y is at the right, so +X corresponds to North in the Vertical projection.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate    System_Definition/Local/Map_Projection_Lander/Vertical/x_axis_maximum  2)/Product_Observational/Observation_Area/Discipline_Area/Cartography/Spatial_Reference_Information/Horizontal_Coordinate    System_Definition/Local/Map_Projection_Lander/Orthorectified/x_axis_maximum		
X_AXIS_MAXIMUMUNIT			ASCII_Real  Units_of_Length	
cart:x_axis_minimum  The x_axis_minimum attribute specifies the value of the X coordinate (measured in the projection frame) of a Vertical, Orthographic or Orthorectified lander map projection at the bottom of the image.  X_AXIS_MINIMUM  SURFACE PROJECTION PARMS.		1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Vertical/x axis min  2)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Orthorectified/x axis	imum phy/Spatial Reference Information/Horizontal Coordinate	
X_AXIS_MINIMUMUNIT			ASCII_Real  Units_of_Length	
cart:y_axis_maximum  SURFACE_PROJECTION_PARMS. Y_AXIS_MAXIMUM SURFACE_PROJECTION_PARMS. Y_AXIS_MAXIMUMUNIT	The y_axis_minimum attribute specifies the value of the Y coordinate (measured in the projection frame) of a Vertical, Orthographic or Orthorectified lander map projection at the right edge of the image.  1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference In System Definition/Local/Map Projection Lander/Orthorectified/y_axis_maximum  2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference In System Definition/Local/Map Projection Lander/Orthorectified/y_axis_maximum		wimum  phy/Spatial Reference Information/Horizontal Coordinate	
			Units_of_Length	
cart:y_axis_minimum  SURFACE_PROJECTION_PARMS. Y_AXIS_MINIMUM SURFACE_PROJECTION_PARMS. Y_AXIS_MINIMUMUNIT	The y_axis_minimum attribute specifies the value of the Y coordinate (measured in the projection frame) of a Vertical, Orthographic or Orthorectified lander map projection at the left edge of the image.	1)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Vertical/y axis min  2)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Orthorectified/y axis	phy/Spatial Reference Information/Horizontal Coordinate	
			Units_of_Length	
cart:zero_elevation_line  SURFACE_PROJECTION_PARMS.  ZERO_ELEVATION_LINE	The zero_elevation_line attribute specifies the image line representing 0.0 degree elevation. Applies to Cylindrical lander map projections.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinal System Definition/Local/Map Projection Lander/Cylindrical/zero elevation line  ASCII_Real		
Alias	The Alias class provides a single alternate name and identification for this product in this or some other archive or data system.	1)/Product Observational/Identification Area/Alias List/Alias  1) alternate id 2) alternate_title 3) comment		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
Alias_List	The Alias_List class provides a list of paired alternate names and identifications for this product in this or some	1)/Product_Observational/Identification_Area/Alias_List	
	other archive or data system.	1) Alias	
Array_2D_Image	The Array 2D Image class is an extension of the Array 2D class and defines a two dimensional image.	1)/Product Observational/File Area Observational/Array 2D Image	
	· · · · · · · · · · · · · · · · · · ·	1) offset 2) axes 3) name 4) local identifier 5) axis index order 6) md5 checksum 7) description 8) Array_2D 9) Display_2D_Image 10) Axis Array 11) Element Array 12) Special Constants 13) Object_Statistics 14) Digital_Object 15) Local Internal Reference	
Array_3D_Image	The Array 3D Image class is an extension of the Array 3D class and defines a three dimensional image.	1)/Product Observational/File Area Observational/Array 3D Image	
	class and defines a time dimensional image.	1) offset 2) axes 3) name 4) local identifier 5) axis index order 6) md5 checksum 7) description 8) Array_3D 9) Axis Array 10) Element Array 11) Special Constants 12) Object_Statistics 13) Digital_Object 14) Local_Internal_Reference	
geom:Articulation_Device_Parameters	The Articulation_Device_Parameters class contains those attributes and sub-classes that describe an articulation	1)/Product Observational/Observation Area/Discipline Area/Geometr	y/Geometry Lander/Articulation Device Parameters[*]
	device. An articulation device is anything that can move independently of the spacecraft to which it is attached. Examples include mast heads, wheel bogies, arms, filter wheel, scan platforms.  InSight Specific: For InSight the articulation devices are ARM and GRAPPLE.	1) geom:device_id 2) geom:device_name 3) geom:device_mode 4) geom:device_phase 5) geom:selected_instrument_id 6) geom:Coordinate_Space_Present 7) Device_Angle 8) Device_Temperature 9) Vector_Device_Gravity	
author_list	The author_list attribute contains a semi-colon-separated list of names of people to be cited as authors of the associated product. The general format for individual	1)/Product_Collection/Identification_Area/Citation_Information/author_list  2)/Product_Document/Identification_Area/Citation_Information/author_list	
		-#	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	names is: SURNAME, GIVEN NAME(s). Initials may be used in lieu of given name(s). If the name contains a suffix ("Jr.", "Sr.", "Ill", etc.) it should be placed before the comma (,). Do not include the word "and" before the final author. All authors should be listed explicitly - do not elide the list using "et al.".		UTF8_Text_Preserved
img:Autoexposure	The Autoexposure class contains attributes used to identify or describe the algorithm used to automatically calculate the proper exposure time. This is generally based on some kind of histogram analysis. The specific autoexposure algorithm used is defined in the processing_algorithm attribute, and the specific set of attributes needed to describe it will vary based on the algorithm. Examples of autoexposure algorithms include "Maki 2003" used on MER, MSL ECAMs, M2020 ECAMS; "Maurice 2012" used on MSL ChemCam; "Smith 1997" used on Mars Pathfinder Imager.	1)/Product Observational/Observation Area/Discipline Area/Imaging/  1) ima:auto exposure data cut 2) ima:active flag 3) ima:auto exposure percent 4) ima:processing venue 5) ima:auto exposure pixel fraction 6) ima:processing algorithm 7) ima:max auto exposure iteration count 8) ima:sequence_number 9) ima:Data_Processing	Commanded Parameters/Exposure/Autoexposure
Axis_Array	The Axis Array class is used as a component of the array class and defines an axis of the array.	1)/Product Observational/File Area Observational/Array 2D Image/A	xis_Array[*]
		2)/Product Observational/File Area Observational/Array 3D Image/Axis Array[*]	
		1) axis name 2) local identifier 3) elements 4) unit 5) sequence number 6) Band_Bin_Set	
axis_index_order	The axis_index_order attribute provides the axis index that varies fastest with respect to storage order.	1)/Product_Observational/File_Area_Observational/Array_2D_Image/a	xis_index_order
		2)/Product Observational/File Area Observational/Array 3D Image/a	xis index order
		1) Last Index Fastest	ASCII_Short_String_Collapsed
axis_name	The axis_name attribute provides a word or combination of words by which the axis is known.	1)/Product Observational/File Area Observational/Array 2D Image/Axis Array[*]/axis name	
		2)/Product Observational/File Area Observational/Array 3D Image/Axis Array[*]/axis name	
			ASCII_Short_String_Collapsed
disp:blue_channel_band	The blue_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by	1)/Product Observational/Observation Area/Discipline Area/Display S	Settings/Color Display Settings/blue channel band
	default, into the blue channel of a display device. The first band along the band axis has band number 1.		ASCII_Integer

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom:c0	The first coefficient of a polynomial.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV  Model/Radial Terms/CO		
		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/C_Model/Entrance_Terms/c0		
		3)/Product Observational/Observation Area/Discipline Area/Geometr Model/Radial Terms/c0	y/Geometry Lander/Camera Model Parameters/CAHVOR	
			ASCII_Real	
geom:c1	The second coefficient of a polynomial.	1)/Product Observational/Observation Area/Discipline Area/Geometr Model/Radial Terms/c1	y/ <u>Geometry Lander/Camera Model Parameters/CAHVORE</u>	
		2)/Product Observational/Observation Area/Discipline Area/GeometrModel/Entrance Terms/c1	y/Geometry Lander/Camera Model Parameters/CAHVORE	
	3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/C Model/Radial Terms/c1		y/Geometry Lander/Camera Model Parameters/CAHVOR	
			ASCII_Real	
geom:c2	The third coefficient of a polynomial.	1)/Product Observational/Observation Area/Discipline Area/Geometr Model/Radial Terms/c2	y/Geometry Lander/Camera Model Parameters/CAHVORE	
		2)/Product_Observational/Observation_Area/Discipline_Area/Geometr Model/Entrance_Terms/c2	y/Geometry Lander/Camera Model Parameters/CAHVORE	
		3)/Product Observational/Observation Area/Discipline Area/Geometr Model/Radial Terms/c2	y/Geometry Lander/Camera Model Parameters/CAHVOR	
			ASCII_Real	
geom:CAHV_Model	The CAHV model is a linear, perspective-projection camera model (equivalent to a pinhole camera). It consists of four 3-vectors (C.A.H.V) that describe the internal and external	1)/Product Observational/Observation Area/Discipline Area/Geometrodel	ry/Geometry Lander/Camera Model Parameters/CAHV M	
	camera model parameters needed to translate between 2D image coordinates and 3D world coordinates. C (Vector_Center) is the 3D position of the pinhole (center of the entrance pupil). A (Vector_Axis) is a unit vector normal to the image plane pointing outward. H (Vector_Horizontal) is a composite vector encoding three quantities: H' (a vector in the image plane perpendicular to the vertical columns), Hs (the distance between the lens center and image plane, measured in horizontal pixels), and Hc (the horizontal image coordinate directly under C when moving parallel to A). V (Vector_Vertical) similarly composites the analogous V', Vs, and Vc in the vertical direction.	1) geom:Vector Center 2) geom:Vector Axis 3) geom:Vector Horizontal 4) geom:Vector Vertical		
geom:CAHVOR_Model	The CAHVOR model is built upon CAHV (see CAHV_Model), adding radial (barrel or pincushion) distortion to the linear	1)/Product Observational/Observation Area/Discipline Area/Geometr Model	y/Geometry Lander/Camera Model Parameters/CAHVOR	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	model. It adds two more 3-vectors to CAHV. O (Vector_Optical) is a unit vector representing the axis of symmetry for the radial distortion. R (Radial_Terms) contains the coefficients of a polynomial function that describes the radial distortion.	1) geom:CAHV Model 2) geom:Vector Optical 3) geom:Vector Center 4) geom:Radial Terms 5) geom:Vector Axis 6) geom:Vector Horizontal 7) geom:Vector Vertical	
geom:CAHVORE_Model	The CAHVORE model is built upon CAHVOR (see CAHVOR_Model), adding support for fisheye lenses. It adds one more 3-vector and two scalars to CAHVOR. E	1)/Product Observational/Observation Area/Discipline Area/Geometric_Model	y/Geometry_Lander/Camera_Model_Parameters/CAHVORE
	(Entrance_Terms) contains the coefficients of a polynomial function used to model movement of the entrance pupil. The two scalars, cahvore_model_type and cahvore_model_parameter, together specify the type of lens being modeled.	1) geom:cahvore_model_type 2) geom:cahvore_model_parameter 3) geom:CAHVOR_Model 4) geom:Entrance_Terms 5) geom:Vector_Optical 6) geom:Vector_Center 7) geom:Radial_Terms 8) geom:Vector_Axis 9) geom:Vector_Horizontal 10) geom:Vector_Vertical	
geom:cahvore_model_parameter  The cahvore_parameter_type attribute is a scalar floati point number used for CAHVORE Type 3 models (see cahvore model type). If the parameter is 1.0, the model type is 1.0, th		1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE Model/cahvore_model_parameter	
	identical to type 1; if 0.0, it is identical to type 2. Most fisheye lenses use a value in between.		ASCII_Real
geom:cahvore_model_type	The cahvore_model_type attribute indicates which variant of the CAHVORE model to use. Type 1 is a perspective-projection model, similar to CAHV and CAHVOR except for the moving entrance pupil. Type 2 is a fish-eye lens model reflecting fundamentally different geometry. Type 3 is a generalization that includes the first two, and is used for most fisheye-type lenses (see cahvore_model_parameter).	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE  Model/cahvore model type	
		1) 1 2) 2 3) 3	ASCII_Integer
cart:Camera_Model_Offset	The Camera_Model_Offset class specifies the location of the image origin with respect to the camera model's origin.	1)/Product Observational/Observation Area/Discipline Area/Cartograp System Definition/Local/Map Projection Lander/Perspective/Camera	
	For CAHV/CAHVOR models, this origin is not the center of the camera, but is the upper-left corner of the "standard"-size image, which is encoded in the CAHV vectors. Applies to the Perspective lander map projection.	1) <u>cart:line</u> 2) <u>cart:sample</u>	
geom:Camera_Model_Parameters	A camera model describes the mathematical relationship between the coordinates of a point in 3-dimensional space	1)/Product Observational/Observation Area/Discipline Area/Geometry	y/Geometry Lander/Camera Model Parameters
	and its projection onto a 2-dimensional image plane. There are numerous types of camera models.	1) geom:model type 2) geom:calibration_source_id 3) geom:solution_id 4) Internal Reference 5) geom:CAHVORE Model 6) geom:Coordinate Space Reference 7) geom:Quaternion Model Transform 8) geom:Vector Model Transform 9) CAHVOR Model 10) CAHV Model	
cart: <b>Cartography</b>		1)/Product Observational/Observation Area/Discipline Area/Cartography	ohy

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
	The Cartography class provides a description of how a 3D sphere, spheroid, or elliptical spheroid or the celestial sphere is mapped onto a plane.	1) cart:Spatial_Domain 2) cart:Spatial_Reference_Information 3) Local_Internal_Reference		
Citation_Information	The Citation_Information class provides specific fields often used in citing the product in journal articles, abstract services, and other reference contexts.	1)/Product Collection/Identification Area/Citation Information  2)/Product File Text/Identification Area/Citation Information		
		3)/Product Document/Identification Area/Citation Information		
		1) author list 2) editor_list 3) publication year 4) doi 5) keyword 6) description		
Collection	The Collection class provides a description of a set of products.	1)/Product_Collection/Collection		
	produces	1) <u>collection_type</u> 2) <u>description</u>		
collection_type	The collection_type attribute provides a classification for the collection.	1)/Product Collection/Collection type		
		1) Browse 2) Calibration 3) Context 4) Data 5) Document 6) Geometry 7) Miscellaneous 8) SPICE Kernel 9) XML Schema	ASCII_Short_String_Collapsed	
disp:color_display_axis	The color_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be	1)/Product Observational/Observation Area/Discipline Area/Display	Settings/Color Display Settings/color display axis	
	displayed in the color dimension of a display device. I.e., bands from this dimension will be loaded into the red, green, and blue bands of the display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.		ASCII_Short_String_Collapsed	
disp:Color_Display_Settings	The Color_Display_Settings class provides guidance to data users on how to display a multi-banded Array object on a	1)/Product_Observational/Observation_Area/Discipline_Area/Display_5	Settings/Color_Display_Settings	
	color-capable display device.	1) disp:color display axis 2) comment 3) disp:red channel band 4) disp:green channel band 5) disp:blue_channel_band		
img:Color_Filter_Array		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Filter Array	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Color_Filter_Array class describes whether or not an image was acquired using a Color Filter Array (CFA) and if so, whether and how the CFA pattern was removed. A CFA is a method for making color images using one exposure on a single sensor plane, where microfilters of different wavelengths are put in front of pixels in a specific pattern. The most common pattern is the Bayer pattern, which has a red, blue, and two green pixels in every 2x2 pixel square. Although generally used for RGB color, CFA filters can be of any number and wavelength (see color_filter_array_type).	1) img:color filter array type 2) img:active flag 3) img:color filter array state 4) img:processing venue 5) img:processing algorithm 6) img:sequence_number 7) img:Data_Processing	
img:color_filter_array_state	Specifies whether the image still has a CFA pattern ("Encoded"), the CFA pattern has been removed	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Filter Array/color filter array state
	("Decoded") or it never had a pattern ("No CFA").	1) Encoded 2) Decoded 3) No CFA	ASCII_Short_String_Collapsed
img:Color_Processing	The Color_Processing class contains parameters describing color correction or processing and how the image is	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing	
	represented in color.	1) ima:color space 2) ima:active flaa 3) ima:color_component 4) ima:processing_venue 5) ima:illuminant 6) ima:processing_algorithm 7) ima:encoded_display_gamma 8) ima:sequence_number 9) ima:Data_Processing 10) ima:Onboard_Responsivity 11) ima:Onboard_Color_Matrix	
msn_surface:Command_Execution	The Command_Execution class contains information about how the command that acquired this data was executed,		
	such as sequence or activity.	1) msn surface:sequence id 2) msn_surface:sequence_version_id 3) msn_surface:sequence_execution_count 4) msn_surface:command_sequence_number 5) msn_surface:command_source_id 6) msn_surface:observation_id 7) msn_surface:request_id	
img:Commanded_Parameters		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Commanded Parameters

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Commanded_Parameters class contains attributes used to identify or describe the commands sent to a spacecraft to perform one or more actions resulting in the acquisition of the current data product. These are distinct from similar values in the root Imaging class which indicate the state of the image as acquired.	1) description 2) imq:Color Filter Array 3) imq:Color Forcessing 4) imq:Detector 5) imq:Downsampling 6) imq:Exposure 7) imq:Flat Field Correction 8) img:Focus 9) img:Focus 9) img:Focus_Stack 10) imq:Frame 11) imq:Onboard Compression 12) img:Optical_Filter 13) imq:Radiometric Correction 14) img:Sampling 15) imq:Shutter Subtraction 16) img:Subframe	
comment	The comment attribute provides one or more remarks or thoughts relevant to the object.	1)/Product Collection/Context Area/comment	
		2)/Product_Collection/Context_Area/Observing_System/Observing_Sys	tem_Component[*]/Internal_Reference/comment
		3)/Product Collection/Context Area/Target Identification/Internal Reference/comment	
		4)/Product File Text/Reference List/Source Product Internal[*]/comment	
		5)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product[*]/Internal Reference/comment	
		6)/Product Observational/Reference List/Source Product Internal[*]/comment	
		7)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product/Internal Reference/comment	
		8)/Product Observational/Identification Area/Alias List/Alias/commen	<u>t</u>
		9)/Product Observational/Observation Area/comment	
		10)/Product Observational/Observation Area/Investigation Area/Inter	rnal_Reference/comment
		11)/Product Observational/Observation Area/Observing System/Obset	rving System Component[*]/Internal Reference/commen
		12)/Product Observational/Observation Area/Target Identification/Int	ernal Reference/comment
		13)/Product Observational/Reference List/Internal Reference/commen	<u>nt</u>
		14)/Product_Observational/Reference_List/Source_Product_Internal/co	mment
		15)/Product Browse/Reference List/Internal Reference/comment	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. VICAR Keyword	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
			ASCII_Text_Preserved
img:Companding	The Companding class describes whether or not data is or has had its bit depth reduced (for example conversion from 12 to 8 bits via a lookup table or bit scaling), the venue where it occurred (Software or Hardware), and the method used to complete the companding. The processing_algorithm attribute specifies how data was companded. Generally this will either be via a lookup table (such as a square root encoding), or by shifting bits to preserve the high order bits and discard the low order bits. The value of this keyword is mission specific but there are recommended values that should apply across missions when possible: NONE - no scaling. LUTn - use the numbered lookup table. Lookup tables are defined in the mission SIS. It is preferred for "n" to be a number but it could be a name, for example LUT_MMM_3 to indicate LUT 3 for the MMM instruments (on MSL). MSB_BITn - Shift to make bit "n" the most significant. Bits start numbering at 0 so MSB_BIT7 means no shift for a 12->8 bit companding, while MSB_BIT11 means to shift for a 12->8 bit companding, while MSB_BIT11 means to shift should be shifted to preserve the highest value. This value should only appear in a command echo; one of the MSB_BITn values should be used in downlinked data to specify what the actual shift was.	1)/Product Observational/Observation Area/Discipline Area/Imaging/IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Sampling/Companding
img:companding_state	The companding_state attribute specifies whether the data is or has had its bit depth reduced, for example conversion from 12 to 8 bits via a lookup table or bit scaling. Valid values: None - values have not been companded. Companded - values are currently companded. Expanded - values have been companded but are now expanded back to original size.	1) / Product_Observational/Observation_Area/Discipline_Area/Imaging/.  1) None 2) Companded 3) Expanded	Sampling/Companding/sompanding_state  ASCII_Short_String_Collapsed
Context_Area	The Context Area provides context information for a product.	1)/Product Collection/Context Area  2)/Product Document/Context Area  1) comment 2) Time Coordinates 3) Primary Result Summary 4) Investigation Area 5) Observing System 6) Target Identification 7) Mission Area 8) Discipline Area	
geom:Coordinate_Space_Definition	The Coordinate_Space classes are typically used for lander/rover geometry while the Coordinate_System construction is used for orbiter/flyby geometry.  InSight Specific:  This class defines the coordinate system in terms of another, reference, coordinate system, providing the offset and rotation between the two.	1)/Product Observational/Observation Area/Discipline Area/Geometro  1) local identifier 2) geom:positive azimuth direction 3) geom:positive elevation direction 4) geom:Coordinate Space Present 5) geom:Vector Origin Offset 6) geom:Quaternion Plus Direction 7) geom:Coordinate Space Reference	y/Geometry Lander/Coordinate Space Definition[*]

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom:Coordinate_Space_Indexed	The Coordinate_Space_Indexed class contains the attributes and classes identifying the indexed coordinate space.	1)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Space February 6   Prod	
		2)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Coordinate Space I	
		3)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Surface Model Parameters/Coordinate Spa	
		4)/Product_Observational/Observation_Area/Discipline_Area/Geometry/Geometry_Lander/Camera_Model_Parameters/Coordinate_Space_Indexed	
		5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry_Lander/Derived_Geometry/Coordinate_Space_Reference/Coordinate_Space_Indexed  6)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate_Space_Definition[1]/Coordinate_Space_Reference/Coordinate_Space_Indexed	
		7)/Product Observational/Observation Area/Discipline Area/Geometric dinate Space Present/Coordinate Space Indexed	y/Geometry Lander/Coordinate Space Definition[*]/Coor
		8)/Product Observational/Observation Area/Discipline Area/Geometrice Reference/Coordinate Space Indexed	y/Geometry Lander/Derived Geometry[*]/Coordinate Spa
		1) geom:coordinate space frame type 2) geom:solution id 3) geom:Coordinate Space Index	
geom:Coordinate_Space_Present	The Coordinate_Space_Present class includes the attributes that identifies the coordinate space presently being defined.		
	Sering definited.	geom:Coordinate_Space_Identification     geom:Coordinate_Space_Indexed	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
geom:Coordinate_Space_Reference	The Coordinate_Space_Reference class includes the attributes that identify the coordinate space being used to express coordinates in the class in which it appears.  InSight Specific: The occurrence in Derived_Product_Parameters specifies the coordinate space used to express pixel values in the file itself (e.g. XYZ values).	2)/Product_Observational/Observation_Area/Discipline_Area/Cartography/Spatial_Reference_Information/Horizontal_Coordin		
copyright	The copyright attribute is a character string giving information about the exclusive right to make copies, license, and otherwise exploit an object, whether physical or digital.	1)/Product_Document/Document/copyright	ASCII_Text_Preserved	
cart: Cylindrical	This is an in-situ projection used for (non-stereo) panoramas. Each image row represents a constant elevation and each image column represents a constant azimuth, from a given point of view. The image scale in degrees per pixel is constant across the image.	1)/Product_Observational/Observation_Area/Discipline_Area/Cartogra_System_Definition/Local/Map_Projection_Lander/Cylindrical  1) cart:pixel_scale_x 2) cart:moximum_elevation 4) cart:minimum_elevation 5) cart:start_azimuth 6) cart:stop_azimuth 7) cart:zero_elevation_line 8) cart:Vector_Projection_Origin	phy/Spatial_Reference_Information/Horizontal_Coordinate	
cart:Cylindrical_Perspective	This is an in-situ projection that is a hybrid. Each column is a vertical slice from a pinhole camera (Perspective	1)/Product_Observational/Observation_Area/Discipline_Area/Cartography/Spatial_Reference_Information/Horizontal_Coordinate_ _System_Definition/Local/Map_Projection_Lander/Cylindrical_Perspective		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	projection), while the columns are spaced evenly in azimuth (Cylindrical projection). It is most useful for viewing panoramas in stereo.	1) cart:pixel scale x 2) cart:pixel scale y 3) cart:maximum elevation 4) cart:minimum elevation 5) cart:projection azimuth 6) cart:projection elevation 7) cart:projection elevation line 8) cart:start azimuth 9) cart:stop azimuth 10) cart:projection_axis_offset 11) cart:Vector_Projection_Origin 12) cart:Vector_Projection_Z_Axis	
geom:Derived_Geometry	The Derived_Geometry class is a container for surface based observations (lander or rover). It is used to provide some geometric quantities relative to a specific Reference Coordinate Space.  InSight Specific:  On InSight, a Derived_Geometry class exists for both Site and Lander frame.	2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived Geometry[*]	
img_surface: <b>Derived_Product_Parameters</b>	The Derived_Product_Parameters class contains attributes used to identify and describe processing performed on products in order to produce a higher level product.	1) imq_surface:derived_image_type_name_ 2) img_surface:horizon_mask_elevation 3) imq_surface:Placement_Target_Instrument 4) imq_surface:Vector_Range_Origin 5) img_surface:Pointing_Correction 6) geom:Coordinate_Space_Reference	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>	
description	The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant	1)/Product Collection/Identification Area/Citation Information/description		
	to the object.	2)/Product Collection/Identification Area/Modification History/Modif	ication Detail/description	
	3)/Product_Collection/File_Area_Inventory/Inventory/Record_Delimited/Field_Delimited[*]/description		d/Field_Delimited[*]/description	
		4)/Product Observational/File Area Observational/Table Delimited[*]	/description	
		5)/Product_Observational/File_Area_Observational/Table_Delimited[*]	/Record_Delimited/Field_Delimited[*]/description	
		6)/Product XML Schema/Identification Area/Modification History/Mo	odification_Detail/description	
		7)/Product_XML_Schema/File_Area_XML_Schema[*]/XML_Schema/des	scription	
		8)/Product_Document/Identification_Area/Modification_History/Modifi	ication_Detail/description	
		9)/Product Document/Document/description  10)/Product File Text/Identification Area/Citation Information/description  11)/Product Document/Identification Area/Citation Information/description  12)/Product Observational/File Area Observational/Header/description		
			UTF8_Text_Preserved	
img:Detector	The Detectorclass contains attributes describing the state of the instrument detector. These are values directly read	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Detector	
	from the detector and do not necessarily reflect the state of the image after onboard processing. For example, the	2)/Product Observational/Observation Area/Discipline Area/Imaging/	Commanded Parameters/Detector	
	entire image may be read into memory and then subframed in software, in which case the subframe attributes in this class reflect the entire image (as read from the detector), whereas those in the Subframe class represent the final subframe results.	1) ima:first_line 2) ima:first_sample 3) ima:lines 4) ima:samples 5) ima:detector to image rotation 6) ima:erase_count 7) ima:readout_rate		
		8) img:gain_mode_id 9) img:gain_number 10) <u>imq:analoq_offset</u>		
geom:Device_Angle  The Device_Angle class is a container for the set of angles between the various components or devices of the spacecraft.  1)/Product Observation Area/Discipline Area/Geometry/Geovice Angle		y/Geometry Lander/Articulation Device Parameters[1]/De		
		1) <u>local identifier</u> 2) <u>geom:Device Angle Index</u>		
geom: <b>Device_Angle_Index</b>		1)/Product Observational/Observation Area/Discipline Area/Geometr vice Angle/Device Angle Index[*]	y/Geometry Lander/Articulation Device Parameters[*]/De	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
	The Device_Angle class is a container for the set of angles the spacecraft device specified in the parent Articulation_Device_Parameters class.	1) geom:index value angle 2) geom:index id 3) geom:List_Index_Angle		
geom: <b>Device_Temperature</b>	The Device_Temperature class is a container for all available device temperatures of an articulated device and/or part(s) of a device.	1)/Product Observational/Observation Area/Discipline Area/Geometrouce Temperature	ry/Geometry Lander/Articulation Device Parameters[*]/De	
		1) <u>local identifier</u> 2) <u>geom:Device Temperature Index</u>		
img:Device_Temperature	The Device_Temperature class provides a container for the temperature of some point on an imaging instrument or other imaging device.	1)/Product Observational/Observation Area/Discipline Area/Imaging/ure[*]	Instrument State/Device Temperatures/Device Temperat	
	InSight Specific: For InSight the arm temperatures are 'AZIMUTH JOINT', 'ELEVATION JOINT', 'ELBOW JOINT', and 'WRIST JOINT'. The grapple temperature is 'GRAPPLE'.	1) img:raw_count 2) imq:temperature value 3) imq:device id 4) img:temperature_status 5) img:Device_Parameters		
attrib some InSigl For In 'ELEV.	The Device_Temperature_Index class specifies the attributes describing the temperature of one device or some part of a device.  InSight Specific:  For InSight the arm temperatures are 'AZIMUTH JOINT', 'ELEVATION JOINT', 'ELBOW JOINT', and 'WRIST JOINT'. The grapple temperature is 'GRAPPLE'.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Articulation Device Parameters[*]/Device Temperature/Device Temperature Index		
		1) geom:index value temperature 2) geom:index value number 3) geom:index_id 4) geom:List_Index_Temperature		
img:Device_Temperatures	The Device_Temperatures class provides a container for the set of temperatures of an imaging instrument or other imaging device.	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Instrument State/Device Temperatures	
		1) <u>img:Device_Temperature</u>		
Discipline_Area	The Discipline area allows the insertion of discipline specific metadata.	1)/Product Observational/Observation Area/Discipline Area	,	
		1) <u>Display Settings</u> 2) <u>Geometry</u> 3) <u>Imaging</u> 4) <u>Surface Imaging</u> 5) <u>Mission Information</u> 6) <u>Surface Mission Information</u> 7) <u>Processing Information</u> 8) <u>Cartography</u>		
disp: <b>Display_Direction</b>	The Display_Direction class specifies how two of the dimensions of an Array object should be displayed in the	1)/Product Observational/Observation Area/Discipline Area/Display	Settings/Display Direction	
	vertical (line) and horizontal (sample) dimensions of a display device.	1) comment 2) disp:horizontal display axis 3) disp:horizontal display direction 4) disp:vertical display axis 5) disp:vertical display direction		
disp:Display_Settings	The Display_Settings class contains one or more classes describing how data should be displayed on a display device.	1)/Product_Observational/Observation_Area/Discipline_Area/Display	Settings	
		1) <u>Local Internal Reference</u> 2) <u>disp:Display Direction</u> 3) <u>disp:Color Display Settings</u> 4) <u>disp:Movie_Display_Settings</u>		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
Document	The Document class describes a document.	1)/Product_Document/Document	
		1) revision_id 2) document_name 3) doi 4) author_list 5) editor_list 6) acknowledgement_text 7) copyright 8) publication_date 9) document_editions 10) description 11) Document_Edition 12) Digital_Object	
Document_Edition	A Document Edition is one complete version of the document in a set of files that is distinguished by language,	1)/Product Document/Document Edition	
	a unique assemblage of file formats, or some other criteria.	1) <u>edition name</u> 2) starting_point_identifier 3) <u>lanauaae</u> 4) <u>files</u> 5) <u>description</u> 6) <u>Document File</u>	
Document_File	The Document File class describes a file which is a part of a document.	1)/Product_Document/Document_Edition/Document_File	
		1) directory_path_name 2) file_name 3) document_standard_id 4) local_identifier 5) creation_date_time 6) file_size 7) records 8) md5_checksum 9) comment 10) file 11) Digital_Object	
document_standard_id		1)/Product Document/Document Edition/Document File/o	locument standard id

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
	The document_standard_id attribute provides the formal name of a standard used for the structure of a document file.	1) 7-Bit ASCII Text 2) Encapsulated Postscript 3) GIF 4) HTML 5) HTML 2.0 6) HTML 3.2 7) HTML 4.0 8) HTML 4.01 9) JPEG 10) LaTEX 11) MPEG-4 12) Microsoft Excel 13) Microsoft Word 14) PDF 15) PDF/A 16) PNG 17) Postscript 18) Rich Text 19) TIFF 20) UTF-8 Text	ASCII_Short_String_Collapsed	
domain  The radial "zone" or "shell" of the target for which the observations were collected or which are represented if the product(s). The value may depend on wavelength_range and size of the target.		1)/Product Collection/Context Area/Primary Result Summary/Science Facets/domain  2)/Product Observational/Observation Area/Primary Result Summary/Science Facets/domain		
	InSight Specific: For InSight camera data, only Surface is used.	1) Atmosphere 2) Dynamics 3) Heliosheath 4) Heliosphere 5) Interior 6) Interstellar 7) Ionosphere 8) Magnetosphere 9) Rings 10) Surface	ASCII_Short_String_Collapsed	
img:Downsampling	The Downsampling class describes whether or not downsampling occurred, the venue where it occurrected	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Downsampling	
	(Software or Hardware), the method used to downsample, and the pixel averaging dimensions. A downsampled image is a smaller version of the image, resulting in reduced resolution of the same coverage area. The processing_algorithm attribute specifies the pixel resolution downsample method used. This varies by mission, but examples from MSL include: 'Mean' - Downsampling done in software by calculation of the mean., 'Conditional' - Use hardware binning if downsampling (by mean calculation) and subframe arguments are consistent.	1) ima:active flaa 2) ima:processing venue 3) ima:processing algorithm 4) ima:sequence_number 5) ima:Data_Processing 6) ima:Pixel_Averaging_Dimensions		
edition_name	The edition name attribute provides a name by which the edition is known.	1)/Product Document/Document Edition/edition name		
			UTF8_Short_String_Collapsed	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
Element_Array	The Element Array class is used as a component of the array class and defines an element of the array.	1)/Product Observational/File Area Observational/Array 2D Image/Element Array		
		2)/Product Observational/File Area Observational/Array 3D Image/E	lement Array	
		1) <u>data type</u> 2) <u>unit</u> 3) <u>scaling factor</u> 4) <u>value offset</u>		
Encoded_Image	The Encoded Image class is used for ancillary images in standard formats, such as JPEG.	1)/Product Observational/File Area Observational Supplemental[*]/En	ncoded Image	
		2)/Product Observational/File Area Observational Supplemental/Enco	oded Image	
		3)/Product Browse/File Area Browse/Encoded Image		
		1) name 2) offset 3) encoding standard id 4) local identifier 5) object length 6) md5 checksum 7) description 8) Encoded_Byte_Stream 9) Digital_Object		
encoding_standard_id	The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded	1)/Product Observational/File Area Observational Supplemental(*)/Encoded Image/encoding standard id		
	Byte Stream digital object.	2)/Product Observational/File Area Observational Supplemental/Enco	oded Image/encoding standard id	
		3)/Product_Browse/File_Area_Browse/Encoded_Image/encoding_stand	lard_id	
		1) GIF 2) J2C 3) JPEG 4) PDF 5) PDF/A 6) PNG 7) TIFF	ASCII_Short_String_Collapsed	
img_surface:Error_Model_Parameter	The Error_Model_Parameter class specifies name and value for a parameter defined by the error model			
	described by the parent class.  InSight Specific:  For MIPL_CONST_DISPARITY_PROJECTED_V1, DELTA_REF_LINE and DELTA_REF_SAMP define how much the reference image was perturbed while DELTA_DISP_LINE and DELTA_DISP_SAMPLE define how much the disparity was perturbed.	1) <u>name</u> 2) value		
img:Exposure	The Exposure class contains attributes identifying the image instrument exposure configuration and image	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Exposure		
	exposure values. As a child of the	2)/Product Observational/Observation Area/Discipline Area/Imaging/	Commanded Parameters/Exposure	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	Image_Product_Information class, these attribute values identify the actual exposure values when the image was taken. As a child of the Commanded_Parameters class, these attribute values are those that were commanded to the spacecraft at the time the image was taken.	1) imq:exposure count 2) imq:exposure duration 3) imq:exposure duration count 4) imq:exposure type 5) imq:Autoexposure	
Field_Delimited	The Field_Delimited class defines a field of a delimited record or a field of a delimited group.	1)/Product Collection/File Area Inventory/Inventory/Record Delimited/Field Delimited[*]	
		2)/Product Observational/File Area Observational/Table Delimited[*]	/Record Delimited/Field Delimited[*]
		1) name 2) field_number 3) data_type 4) maximum_field_length 5) field_format 6) unit 7) scaling_factor 8) value_offset 9) description 10) Special_Constants 11) Field_Statistics	
field_delimiter	The field_delimiter attribute provides the character that marks the boundary between two fields in a delimited	1)/Product Collection/File Area Inventory/Inventory/field delimiter	
	table.	2)/Product Observational/File Area Observational/Table Delimited[*]	/field_delimiter
		1) Comma 2) Horizontal Tab 3) Semicolon 4) Vertical Bar 5) comma 6) horizontal tab 7) semicolon 8) vertical bar	ASCII_Short_String_Collapsed
field_number	The field_number attribute provides the position of a field, within a series of fields, counting from 1. If two fields	d, 1)/Product Collection/File Area Inventory/Inventory/Record Delimited/Field Delimited[*]/field number	
	within a record are physically separated by one or more groups, they have consecutive field numbers; the fields	2)/Product Observational/File Area Observational/Table Delimited[*]/Record Delimited/Field Delimited[*]/field number	
Fie	within the intervening group(s) are numbered separately. Fields within a group separated by one or more (sub)groups, will also have consecutive field numbers.		ASCII_NonNegative_Integer
fields	The fields attribute provides a count of the total number of scalar fields directly associated with a table record. Fields within groups within the record are not included in this count.	-// <u></u>	
I -		2)/Product Observational/File Area Observational/Table Delimited[*]	/Record_Delimited/fields
			ASCII_NonNegative_Integer

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
File	The File class consists of attributes that describe a file in a data store.	1)/Product Collection/File Area Inventory/File		
		2)/Product Observational/File Area Observational Supplemental[*]/Fi	<u>le</u>	
		3)/Product_XML_Schema/File_Area_XML_Schema[*]/File		
		4)/Product File Text/File Area Text/File		
		5)/Product Observational/File Area Observational/File		
		6)/Product Observational/File Area Observational Supplemental/File		
		7)/Product_Browse/File_Area_Browse/File		
		1) file name 2) local identifier 3) creation date time 4) file size 5) records 6) md5_checksum 7) comment 8) Digital_Object		
File_Area_Browse	The File Area Browse class describes a file and one or more tagged_data_objects contained within the file.	1)/Product Browse/File Area Browse		
		1) File_Area 2) <u>File</u> 3) Array 4) <u>Encoded Image</u>		
File_Area_Inventory	The File Area Inventory class describes a file and an inventory consisting of references to members.	1)/Product Collection/File Area Inventory		
		1) File_Area 2) File 3) Inventory		
File_Area_Observational	The File Area Observational class describes, for an observational product, a file and one or more	1)/Product Observational/File Area Observational		
	tagged_data_objects contained within the file.	1) File_Area 2) File 3) Composite_Structure 4) Array 5) Header 6) Array 3D Image 7) Array 2D Image 8) Table Delimited		
File_Area_Observational_Supplemental	The File Area Observational Supplemental class describes, for an observational product, additional files and	1)/Product Observational/File Area Observational Supplemental[*]		
	tagged_data_objects contained within the file.	2)/Product Observational/File Area Observational Supplemental		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
		1) File_Area 2) File 3) Composite_Structure 4) Array 5) Encoded_Image 6) Stream_Text	
File_Area_Text	The File Area Text class describes a file that contains a text stream object.	1)/Product File Text/File Area Text	
	Stream object.	1) File_Area 2) File 3) Stream_Text	
File_Area_XML_Schema	The File Area XML Schema class describes a file that contains a resource used for the PDS4 implementation into	1)/Product XML Schema/File Area XML Schema[*]	
	XML.	1) File_Area 2) <u>File</u> 3) <u>XML Schema</u>	
file_size	The file_size attribute provides the size of the file.	1)/Product Collection/File Area Inventory/File/file size	
		2)/Product XML Schema/File Area XML Schema(*1/File/file_size	
			ASCII_NonNegative_Integer
			Units_of_Storage
files	The files attribute provides the number of files in the edition.	1)/Product Document/Document Edition/files	
			ASCII_NonNegative_Integer
img:Flat_Field_Correction	The Flat_Field_Correction class specifies how flat-field correction was performed on this image. This can be done	1)/Product Observational/Observation Area/Discipline Area/Imaging/Flat Field Correction	
	either algorithmically, using a Radial_Flat_Field_Correction, or using a Flat_Field_File.	1) img:active flaa 2) img:processing venue 3) img:processing algorithm 4) img:sequence_number 5) img:Data_Processing 6) img:Radial_Flat_Field_Function 7) img:Flat_Field_File	
img:Flat_Field_File	The Flat_Field_File class specifies the image used for flat field correction. The image is divided by this flat field	1)/Product Observational/Observation Area/Discipline Area/Imaging/Flat Field Correction/Flat Field File	
	image in order to apply the flat field correction (which is the opposite of Radial_Flat_Field_Function).	1) description 2) name 3) img:Data_Processing_File 4) External_Reference 5) Internal_Reference	
img: <b>Frame</b>	The Frame class contains attributes providing information specific to an image frame. A frame consists of a sequence of measurements made over a specified time interval, and may include measurements from different instrument modes.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Frame	
		1) img:frame id 2) img:frame type name	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom: <b>Geometry</b>	The Geometry class is a container for all geometric information in the label. The Image_Display_Geometry class should have one instance if the primary data object is an Array object for which two of the dimensions are suitable for display in the vertical (line) and horizontal (sample) dimensions of a display device. Multiple instances of the Image_Display_Geometry class are only appropriate if the data product contains multiple Array objects and the orientations of the various objects are not the same.	1)/Product_Observational/Observation_Area/Discipline_Area/Geometr	x
		1) geom:SPICE Kernel Files 2) geom:Expanded_Geometry 3) geom:Image_Display_Geometry 4) geom:Geometry_Orbiter 5) geom:Geometry_Lander	
geom: <b>Geometry_Lander</b>	The Geometry_Lander class is a container for all geometric information in the label relating to a landed spacecraft,	1)/Product Observational/Observation Area/Discipline Area/Geometr	y/ <u>Geometry_Lander</u>
	including rovers.	1) geom:Articulation Device Parameters 2) geom:Camera Model Parameters 3) geom:Coordinate Space Definition 4) geom:Derived Geometry 5) geom:Motion Counter	
img_surface: <b>Geometry_Projection</b>	The Geometry_Projection describes the geometric		
	projection or warping the image has undergone. It is not the intent of this class to describe map projections, but rather image warps such as linearization (stereo epipolar alignment), geometric sensor correction, or rubbersheeting. If present, a linearization partner image can be referenced using either an Internal_Reference or External_Reference.	1) ima surface:linearization mode 2) ima surface:linearization mode fov 3) ima surface:geometry projection type 4) External_Reference	
disp:green_channel_band	The green_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by	1)/Product Observational/Observation Area/Discipline Area/Display Settings/Color Display Settings/green channel band	
	default, into the green channel of a display device. The first band along the band axis has band number 1.		ASCII_Integer
groups	The groups attribute provides a count of the total number of groups directly associated with a table record. Groups	1)/Product Collection/File Area Inventory/Inventory/Record Delimited/groups	
	within groups within the record are not included in this count.	2)/Product Observational/File Area Observational/Table Delimited(*)/Record Delimited/groups	
			ASCII_NonNegative_Integer
Header	The Header class describes a data object header. InSight Specific:	1)/Product Observational/File Area Observational/Header	
	For InSight this identifies the attached VICAR label for images and specifies its length.	1) name 2) object length 3) offset 4) local identifier 5) parsing standard id 6) md5_checksum 7) description 8) Parsable_Byte_Stream 9) Digital_Object	
cart:Horizontal_Coordinate_System_Definition	The Horizontal_Coordinate_System_Definition class provides the reference frame or system from which linear or angular quantities are measured and assigned to the position that a point occupies.	1)/Product Observational/Observation Area/Discipline Area/Cartogra <u>System Definition</u>	phy/Spatial Reference Information/Horizontal Coordinate
		1) cart:Geographic 2) cart:Geodetic_Model 3) Local	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
disp:horizontal_display_axis	The horizontal_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be displayed in the horizontal or "sample" dimension on a display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.	1)/Product Observational/Observation Area/Discipline Area/Display	Settings/Display Direction/horizontal display axis
			ASCII_Short_String_Collapsed
disp:horizontal_display_direction	The horizontal_display_direction attribute specifies the direction across the screen of a display device that data	1)/Product Observational/Observation Area/Discipline Area/Display	Settings/Display Direction/horizontal_display_direction
	along the horizontal axis of an Array is supposed to be displayed.  InSight Specific:  InSight data is always Left to Right.	1) Left to Right 2) Right to Left	ASCII_Short_String_Collapsed
Identification_Area	The identification area consists of attributes that identify and name an object.	1)/Product Collection/Identification Area	
		2)/Product XML Schema/Identification Area	
		3)/Product File Text/Identification Area	
		4)/Product Document/Identification Area	
		5)/Product Observational/Identification Area	
		6)/Product Browse/Identification Area	
		1) logical identifier 2) version id 3) title 4) information model version 5) product class 6) Alias List 7) Citation Information 8) Modification History	
img_surface:Image_Identifiers	The Image_Identifiers class contains items that help to identify the image or guide how processing should be done to the image.		
		1) <u>img surface:image id</u> 2) <u>img surface:mosaic id</u> 3) <u>img surface:mesh id</u> 4) <u>img surface:stereo match id</u>	
img: <b>Imaging</b>		1)/Product Observational/Observation Area/Discipline Area/Imaging	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Imaging class contains classes and attributes describing both the image product itself and the imaging instrument. Image product information can include exposure duration, filters, data correction, sampling, frame, sub-frames, and how the product was derived. For the imaging instrument, information can be provided describing the dynamic physical or operating characteristics of the imaging instrument.	1) Local Internal Reference 2) ima:Color Filter Array 3) ima:Color Processing 4) ima:Detector 5) ima:Downsamplina 6) ima:Exposure 7) ima:Flat Field Correction 8) img:Focus 9) img:Focus 5) img:Onboard Compression 12) img:Onboard Compression 12) img:Ontical Filter 13) ima:Radiometric Correction 14) ima:Samplina 15) ima:Shutter Subtraction 16) ima:Subframe 17) img:Video 18) ima:Instrument State 19) img:Commanded Parameters	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>	
geom:index_id	The index_id attribute supplies a short name (identifier) for the associated value in a group of related values.	1)/Product Observational/Observation Area/Discipline Area/Surface eference/Coordinate Space Indexed/Coordinate Space Indexef* /indexed/Coordinate Space Indexef*		
		2)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Space R eference/Coordinate Space Index/Index id		
		3)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Coordinate Space dex/index id		
		4)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Surface Model Parameters/Coordinate Spa e Index/index id		
		5)/Product Observational/Observation Area/Discipline Area/Geometre Space Reference/Coordinate Space Indexed/Coordinate Sp		
		6)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate  System Definition/Local/Map Projection Lander/Coordinate Space Reference/Coordinate Space Indexed/Coordinate Space Idex[*]/index id  7)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate  System Definition/Local/Surface Model Parameters/Coordinate Space Reference/Coordinate Space Indexed/Coordinate Indexed/Coordinate Indexed/Coordinate Indexed/Coordinate Indexed/Coordinate Indexed/Coordinate Indexed/Coordinate Indexed/Coordina		
		8)/Product Observational/Observation Area/Discipline Area/Geometre Space Reference/Coordinate Space Indexed/Coordinate Sp		
		9)/Product Observational/Observation Area/Discipline Area/Geometra Reference/Coordinate Space Indexed/Coordinate Space Index/index		
		10)/Product Observational/Observation Area/Discipline Area/Geome evice Angle/Device Angle Index[*]/index id	try/Geometry Lander/Articulation Device Parameters[*]/D	
		11)/Product Observational/Observation Area/Discipline Area/Geome evice Temperature/Device Temperature Index/index id	try/Geometry_Lander/Articulation_Device_Parameters[*]/D	
		12)/Product Observational/Observation Area/Discipline Area/Geome rdinate Space Reference/Coordinate Space Indexed/Coordinate Space		
		13)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space Definition[*]/Coordinate Space Present/Coordinate Space Indexed/Coordinate Space Indexef*]/Index id  14)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived Geometry[*]/Coordinate Space Indexef/Coordinate Spac		
		15)/Product Observational/Observation Area/Discipline Area/Geome dex[*]/index id	try/Geometry Lander/Motion Counter/Motion Counter In	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
			ASCII_Short_String_Collapsed
information_model_version	The information_model_version attribute provides the version identification of the PDS Information Model on which the label and schema are based.	1)/Product Collection/Identification Area/information model version  2)/Product XML Schema/Identification Area/information model version  3)/Product File Text/Identification Area/information model version  4)/Product Document/Identification Area/information model version  5)/Product Observational/Identification Area/information model version  5)/Product Browse/Identification Area/information model version  1) 1.0.0.0  2) 1.1.0.0  3) 1.10.0.0  4) 1.10.1.0  5) 1.11.0.0  6) 1.12.0.0  7) 1.2.0.0  8) 1.2.0.1  9) 1.3.0.0  10) 1.3.0.1  11) 1.4.0.0  12) 1.5.0.0  13) 1.6.0.0  14) 1.7.0.0  15) 1.8.0.0  16) 1.9.0.0	
proc:Input_Product_List	The Input_Product_List class describes all of the product(s)	17) 1.9.1.0  1)/Product Observational/Observation Area/Discipline Area/Processin	ng Information/Input Product List
	most directly used as input to software for product creation, including raw, partially-processed, calibrated, or derived products. These Input Products can be explicitly described in this label using the Input_Product class, and/or a list of products can be specified in another product referenced by the Internal_Reference or Local_Internal_Reference.	1) proc:Input_Product	
img_surface:Instrument_Information	The Instrument_Information class specifies information about the configuration of the instrument as it acquired this observation.	1) imq surface:image type 2) img_surface:image_acquire_mode 3) imq surface:instrument type 4) img_surface:instrument mode_id 5) img_surface:instrument serial_number 6) imq surface:instrument version number 7) imq surface:ops_instrument key 8) img_surface:camera_product_id 9) img_surface:camera_product_id_count	
img:Instrument_State		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Instrument State

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
	The Instrument_State class contains classes providing the values of any dynamic physical or operating characteristics of the imaging instruments.	1) img:Device_Component_States 2) img:Device_Currents 3) img:Device_Motor_Counts 4) img:Device_Temperatures 5) img:Device_Voltages		
Internal_Reference	The Internal_Reference class is used to cross-reference other products in PDS4-compliant registries of PDS and its	1)/Product Collection/Context Area/Investigation Area/Internal Reference		
	recognized international partners.	2)/Product_Collection/Context_Area/Observing_System/Observing_Sys	tem_Component[*]/Internal_Reference	
		3)/Product_Collection/Context_Area/Target_Identification/Internal_Ref	erence	
		4)/Product_Collection/Reference_List/Internal_Reference[*]		
		5)/Product Document/Reference List/Internal Reference[*]		
		6)/Product_Document/Context_Area/Investigation_Area/Internal_Reference	rence	
		7)/Product_Document/Context_Area/Observing_System/Observing_Sys	tem_Component/Internal_Reference	
		8)/Product_Observational/Observation_Area/Discipline_Area/Surface_I		
		9)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Stereo Product Parameters/Internal Reference		
		10)/Product Observational/Observation Area/Discipline Area/Processinal Reference	ing Information/Input Product List/Input Product[*]/Inter	
		11)/Product Observational/Observation Area/Discipline Area/Surface Instrument/Internal Reference	Imaging/Derived Product Parameters/Placement Target	
		12)/Product Observational/Observation Area/Discipline Area/Imaging	Flat Field Correction/Flat Field File/Internal Reference	
		13)/Product Observational/Observation Area/Discipline Area/Processi   Reference	ing Information/Input Product List/Input Product/Interna	
		14)/Product Observational/Observation Area/Investigation Area/Inter	rnal Reference	
		15)/Product_Observational/Observation_Area/Observing_System/Observing_Syst	rving System Component[*]/Internal Reference	
		16)/Product Observational/Observation Area/Target Identification/Int	ternal Reference	
		17)/Product_Observational/Reference_List/Internal_Reference		
		18)/Product Browse/Reference List/Internal Reference		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
		1) <u>lid reference</u> 2) <u>reference type</u> 3) <u>comment</u> 4) <u>lidvid reference</u>	
Inventory	The Inventory class defines the inventory for members of a collection.	1)/Product Collection/File Area Inventory/Inventory	
	Concedion	1) name 2) reference type 3) offset 4) records 5) local identifier 6) object lenath 7) record delimiter 8) md5 checksum 9) parsing standard id 10) description 11) field delimiter 12) Table Delimited 13) Digital_Object 14) Uniformly_Sampled 15) Record_Delimited	
Investigation_Area	The Investigation_Area class provides information about an investigation (mission, observing campaign or other coordinated, large-scale data collection effort).	1)/Product Collection/Context Area/Investigation Area  2)/Product Document/Context Area/Investigation Area	
		3)/Product Observational/Observation Area/Investigation Area	
		1) <u>name</u> 2) <u>type</u> 3) <u>Internal_Reference</u>	
img:JPEG_Parameters	The JPEG_Parameters class contains attributes describing onboard compression parameters specific to Joint	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Onboard Compression/IPEG Parameters
	Photographic Experts Group (JPEG) image compression.	1) <u>img:color subsampling mode</u> 2) <u>img:jpeg quality</u> 3) img:jpeg_parameter	
keyword	The keyword attribute provides one or more words to be used for keyword search.	1)/Product_Collection/Identification_Area/Citation_Information/keyword[*]	
	asea for neyword scarcin.		UTF8_Short_String_Collapsed
language	The language attribute provides the language used for definition and designation of the term.	1)/Product_Document/Document_Edition/language	
		1) English	ASCII_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. VICAR Keyword	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
cart:line	The line attribute specifies the line number in the image.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Vertical/Pixel Position Origin/line  2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Orthorectified/Pixel Position Origin/line		
		3)/Product Observational/Observation Area/Discipline Area/Cartogra System Definition/Local/Map Projection Lander/Perspective/Camera	phy/Spatial Reference Information/Horizontal Coordinate  Model Offset/line	
			ASCII_Real	
img_surface:linearization_mode	The linearization_mode attribute specifies what kind of stereo partner was used to linearize the image (the			
	process requires two camera models).	1) Nominal 2) Actual 3) None	ASCII_Short_String_Collapsed	
cart: <b>Local</b>	The Local class provides a description of any coordinate system that is not aligned with the surface of the planet.	1)/Product Observational/Observation Area/Discipline Area/Cartogramusystem Definition/Local	phy/Spatial Reference Information/Horizontal Coordinate	
		1) <u>cart:local_description</u> 2) <u>cart:local_georeference_information</u> 3) <u>Map_Projection_Lander</u> 4) <u>Surface_Model_Parameters</u>		
cart:local_description	The local_description attribute provides a description of the coordinate system and its orientation to the surface of a planet.	1)/Product Observational/Observation Area/Discipline Area/Cartogra <u>System Definition/Local/local description</u>	phy/Spatial_Reference_Information/Horizontal_Coordinate	
	a planet.		ASCII_Text_Preserved	
local_identifier	The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.	1)/Product Collection/File Area Inventory/File/local identifier  2)/Product Collection/File Area Inventory/Inventory/local identifier		
		3)/Product Observational/File Area Observational/Array 2D Image/Id	ocal identifier	
		4)/Product Observational/Observation Area/Discipline Area/Geometridentifier[*]	y/Geometry_Lander/Coordinate_Space_Definition[*]/local_	
		5)/Product Observational/File Area Observational/Header/local identifier  6)/Product Observational/File Area Observational/Array 3D Image/local identifier  7)/Product Browse/File Area Browse/File/local identifier		
8)/Product_Browse/File_Area_Browse/Encoded_Image/local_identifier				
			ASCII_Local_Identifier	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
Local_Internal_Reference	The Local Internal_Reference class is used to cross- reference other Description Objects in a PDS4 label.	1)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Coordinate Speference/Local Internal Reference		
		2)/Product Observational/Observation Area/Discipline Area/Cartography/Local Internal Reference  3)/Product Observational/Observation Area/Discipline Area/Disc		
	4)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Mode te Space Reference/Local Internal Reference			
	5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Coordinate Space dinate Space Reference/Local Internal Reference			
		6)/Product Observational/Observation Area/Discipline Area/Geometr ce Reference/Local Internal Reference	y/Geometry_Lander/Derived_Geometry[1]/Coordinate_Spa	
		7)/Product Observational/Observation Area/Discipline Area/Imaging/	Local Internal Reference	
		8)/Product_Observational/Observation_Area/Discipline_Area/Processin	ng_Information/Local_Internal_Reference	
		1) <u>comment</u> 2) <u>local identifier reference</u> 3) <u>local reference type</u>		
local_reference_type	The local_reference_type attribute provides the name of an association between an entity identified by a local_identifier_reference and another corresponding	1)/Product Observational/Observation Area/Discipline Area/Surface eference/Local Internal Reference/local reference type	maging/Derived Product Parameters/Coordinate Space R	
	entity identified by a local_identifier. The values for the local_reference_type are expected to be enumerated for	2)/Product Observational/Observation Area/Discipline Area/Cartogra	ohy/Local Internal Reference/local reference type	
	appropriate contexts in the Schematron files of local (i.e., discipline and mission) data dictionaries.  InSight Specific:	3)/Product_Observational/Observation_Area/Discipline_Area/Display :	Settings/Local_Internal_Reference/local_reference_type	
	Values used for InSight include cartography_parameters_to_image_object, imaging_parameters_to_image_object, processing_information_to_data_object,	4)/Product Observational/Observation Area/Discipline Area/Geometr te Space Reference/Local Internal Reference/local reference type	y/Geometry Lander/Camera Model Parameters/Coordina	
	to_reference_coordinate_space, display_settings_to_array.	5)/Product Observational/Observation Area/Discipline Area/Geometr dinate Space Reference/Local Internal Reference/local reference typ		
		6)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Derived Geometry[1]/Coordinate Spce Reference/Local Internal Reference/local reference type		
		7)/Product Observational/Observation Area/Discipline Area/Imaging/Local Internal Reference/local reference type		
		8)/Product Observational/Observation Area/Discipline Area/Processing Information/Local Internal Reference/local reference		
			ASCII_Short_String_Collapsed	
local_true_solar_time		1)/Product Observational/Observation Area/Time Coordinates/local to	rue solar time	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
	The local_true_solar_time (LTST) attribute provides the local time on a rotating solar system body where LTST is 12 h at the sub-solar point (SSP) and increases 1 h for each 15 degree increase in east longitude away from the SSP for prograde rotation.		ASCII_Short_String_Collapsed
cart:Map_Projection_Lander	The Map_Projection class provides the systematic representation of all or part of the surface of a planet on a	1)/Product_Observational/Observation_Area/Discipline_Area/Cartogra_ System_Definition/Local/Map_Projection_Lander	nphy/Spatial_Reference_Information/Horizontal_Coordinate
	plane or developable surface from the perspective of an insitu spacecraft.	1) cart:lander_map_projection_name 2) cart:Cylindrical 3) geom:Coordinate_Space_Reference 4) Cylindrical_Perspective 5) Orthorectified 6) Vertical	
maximum_field_length	The maximum_field_length attribute sets an upper, inclusive bound on the number of bytes in the field.	1)/Product Collection/File Area Inventory/Inventory/Record Delimite	ed/Field_Delimited[*]/maximum_field_length
	inclusive bound on the number of bytes in the field.		ASCII_NonNegative_Integer
			Units_of_Storage
maximum_record_length	The maximum_record_length attribute provides the maximum length of a record, including the record	1)/Product Collection/File Area Inventory/Inventory/Record Delimited/maximum record length	
	delimiter.		ASCII_NonNegative_Integer
			Units_of_Storage
md5_checksum	The md5_checksum attribute is the 32-character hexadecimal number computed using the MD5 algorithm	1)/Product Collection/File Area Inventory/File/md5 checksum	
	for the contiguous bytes of single digital object (as stored) or for an entire file.		ASCII_MD5_Checksum
Mission_Area	The mission area allows the insertion of mission specific metadata.	1)/Product Observational/Observation Area/Mission Area	1
msn:Mission_Information	The Mission Information class provides a set of optional		
	attributes that have their value sets defined by the mission.	1) msn:mission phase name 2) msn:mission_phase_identifier 3) msn:start_orbit_number 4) msn:stop_orbit_number 5) msn:spacecraft_clock_start_count 6) msn:spacecraft_clock_stop_count	
modification_date	The modification_date attribute provides date the modifications were completed	1)/Product Collection/Identification Area/Modification History/Modification Detail/modification date  2)/Product XML Schema/Identification Area/Modification History/Modification Detail/modification date  3)/Product Document/Identification Area/Modification History/Modification Detail/modification date	
			ASCII_Date_YMD

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
Modification_Detail	The Modification_Detail class provides the details of one round of modification for the product. The first, required, instance of this class documents the date the product was first registered.  InSight Specific: For InSight, information about the first registration of the product is not available at the time the label is created, and it is not feasible to update the label later. Therefore, the single (required) instance of Modification_Detail instead specifies the version number of the current version, and the date the label was created (not the date it was added to the PDS registry, which is similarly unavailable).	1)/Product Collection/Identification Area/Modification History/Modification Listory/Modification Listory/Modificat	odification_Detail
Modification_History	The Modification_History class tracks the history of changes made to the product once it enters the registry system.	1)/Product Collection/Identification Area/Modification History  2)/Product XML Schema/Identification Area/Modification History  3)/Product Document/Identification Area/Modification History  1) Modification Detail	
geom:Motion_Counter	The Motion_Counter class provides a set of integers that describe a (potentially) unique location (position / orientation) for a rover or other movable object. Each time an event occurs that results in a movement, a new motion counter value is created. This includes intentional motion due to drive commands, as well as potential motion due to other articulating devices, such as arms or antennae. This motion counter (or part of it) is used as a reference to define instances of coordinate systems that can move such as SITE or ROVER frames. The motion counter is defined in a mission-specific manner. Although the original intent was to have incrementing indices (e.g., MER), the motion counter could also contain any integer values that conform to the above definition, such as time or spacecraft clock values.	1)/Product_Observational/Observation_Area/Discipline_Area/Geometr  1) name 2) local_identifier 3) geom:Motion_Counter_Index	y/Geometry_Lander/Motion_Counter
geom:Motion_Counter_Index	The Motion_Counter_Index class identifies and populates one element of a Motion_Counter list. The class should be repeated for each element of the list.  InSight Specific:  InSight supports only two motion counter indices: SITE and DRIVE. Although the lander is not supposed to move, these are included for legacy software reasons.	1) geom:index_value_number 2) geom:index_id	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>	
name	The name attribute provides a word or combination of words by which the object is known.	1)/Product Collection/Context Area/Investigation Area/name  2)/Product Collection/Context Area/Observing System/Observing System Component[*]/name  3)/Product Collection/Context Area/Target Identification/name  4)/Product Collection/File Area Inventory/Inventory/Record Delimited/Field Delimited[*]/name		
		5)/Product_Observational/Observation_Area/Observing_System/name		
		6)/Product Observational/File Area Observational/Table Delimited[*]	/name	
		7)/Product_Observational/File_Area_Observational/Table_Delimited[*]	/Record_Delimited/Field_Delimited[*]/name	
		8)/Product_XML_Schema/File_Area_XML_Schema[*]/XML_Schema/nan	n <u>e</u>	
		9)/Product Document/Context Area/Investigation Area/name  10)/Product Document/Context Area/Observing System/name  11)/Product Document/Context Area/Observing System/Observing System Component/name  12)/Product Observational/Observation Area/Investigation Area/name		
		13)/Product Observational/Observation Area/Observing System/Obse	rving System Component[*]/name	
		14)/Product_Observational/Observation_Area/Target_Identification/na	me_	
			UTF8_Short_String_Collapsed	
Observation_Area	The observation area consists of attributes that provide information about the circumstances under which the data	1)/Product Observational/Observation Area		
	were collected.	1) <u>comment</u> 2) <u>Context Area</u> 3) <u>Time Coordinates</u> 4) <u>Primary Result Summary</u> 5) <u>Investigation Area</u> 6) <u>Observing System</u> 7) <u>Target Identification</u> 8) <u>Mission Area</u> 9) <u>Discipline Area</u>		
Observing_System	The Observing System class describes the entire suite used to collect the data.	sed 1)/Product Collection/Context Area/Observing System		
2)/Product Document/Context Area/Observing System				
		3)/Product Observational/Observation Area/Observing System		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
		1) <u>name</u> 2) <u>description</u> 3) <u>Observing System Component</u> 4) Conceptual_Object	
Observing_System_Component	The Observing System Component class describes one or more subsystems used to collect data.	1)/Product Collection/Context Area/Observing System/Observing System Component[*]	
		2)/Product_Document/Context_Area/Observing_System/Observing_Sys	stem_Component
		3)/Product Observational/Observation Area/Observing System/Obser	ving System Component[*]
		1) name 2) type 3) description 4) Internal Reference 5) External_Reference	
img:onboard_B_b	Specifies the factor that has been multiplied by the B pixel value after de-Bayering (demosaicking) takes place. This	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Processing/Onboard Color Matrix/onboard B b
	value is summed with the multiplied R and G pixel values to produce the output Blue value.		ASCII_Real
img:onboard_B_g	Specifies the factor that has been multiplied by the G pixel value after de-Bayering (demosaicking) takes place. This	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing/Onboard Color Matrix/onboard B g	
	value is summed with the multiplied R and B pixel values to produce the output Blue value.		ASCII_Real
img:onboard_B_r	Specifies the factor that has been multiplied by the R pixel value after de-Bayering (demosaicking) takes place. This	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing/Onboard Color Matrix/onboard B r	
	value is summed with the multiplied G and B pixel values to produce the output Blue value.		ASCII_Real
img:Onboard_Compression	The Onboard_Compression class contains attributes describing the compression performed onboard a	1)/Product Observational/Observation Area/Discipline Area/Imaging/Onboard Compression	
	spacecraft or instrument for data storage and transmission.	1) img:onboard compression class 2) img:onboard compression mode 3) img:onboard compression type 4) img:onboard compression rate 5) img:onboard compression ratio 6) img:onboard_compression_quality 7) img:deferred_flag 8) img:error_pixel_count 9) img:ICER_Parameters 10) IPEG_Parameters	
img:onboard_compression_class	The onboard_compression_class attribute identifies the type of on-board compression used for data storage and	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Onboard Compression/onboard compression class
identi examı gives	transmission. Note that the onboard_compression_type identifies the specific compression algorithm used (for example, ICER), whereas the onboard_compression_class gives a simple indicator of the type of compression mode. Valid values: 'Lossless', 'Lossy', 'Uncompressed'	1) Lossless 2) Lossy 3) Uncompressed	ASCII_Short_String_Collapsed
img:onboard_G_b		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Processing/Onboard Color Matrix/onboard G b

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	Specifies the factor that has been multiplied by the B pixel value after de-Bayering (demosaicking) takes place. This value is summed with the multiplied R and G pixel values to produce the output Green value.		ASCII_Real
img:onboard_G_g	Specifies the factor that has been multiplied by the G pixel value after de-Bayering (demosaicking) takes place. This	1)/Product Observational/Observation Area/Discipline Area/Imaging/	Color Processing/Onboard Color Matrix/onboard G g
	value is summed with the multiplied R and B pixel values to produce the output Green value.		ASCII_Real
img:onboard_G_r	Specifies the factor that has been multiplied by the R pixel value after de-Bayering (demosaicking) takes place. This	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/	Color Processing/Onboard Color Matrix/onboard G r
	value is summed with the multiplied G and B pixel values to produce the output Green value.		ASCII_Real
img:onboard_R_b	Specifies the factor that has been multiplied by the B pixel value after de-Bayering (demosaicking) takes place. This	1)/Product_Observational/Observation_Area/Discipline_Area/Imaging/Color_Processing/Onboard_Color_Matrix/onboard_R_b	
	value is summed with the multiplied R and G pixel values to produce the output Red value.		ASCII_Real
img:onboard_R_g	Specifies the factor that has been multiplied by the G pixel value after de-Bayering (demosaicking) takes place. This value is summed with the multiplied R and B pixel values to produce the output Red value.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing/Onboard Color Matrix/onboard R g	
			ASCII_Real
img:onboard_R_r	Specifies the factor that has been multiplied by the R pixel value after de-Bayering (demosaicking) takes place. This value is summed with the multiplied G and B pixel values to produce the output Red value.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Color Processing/Onboard Color Matrix/onboard R r	
			ASCII_Real
cart: Orthorectified	This is an in-situ projection that provides a true overhead view of the scene. Range data is required to create this	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinal System Definition/Local/Map Projection Lander/Orthorectified	
	projection, meaning there is no parallax distortion. It has a constant scale in meters/pixel.	1) cart:pixel resolution x 2) cart:pixel resolution y 3) cart:x axis maximum 4) cart:x axis minimum 5) cart:y axis maximum 6) cart:y axis minimum 7) cart:Pixel Position Origin 8) cart:Vector Projection Origin 9) cart:Vector Projection Y_Axis 10) cart:Vector_Projection_Z_Axis 11) cart:Vector_Projection_Z_Axis	
proc: <b>Parameter</b>	The Parameter class describes any information about software program execution. Examples of information that	1)/Product Observational/Observation Area/Discipline Area/Processing Information/Process/Software/Software Program/Soft ware Program Parameters/Parameter[*]	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	can be captured here are software input arguments, software output arguments, log information, and references to specific data products. This class is intended to be freeform to allow data providers the ability to specify information they determine applicable and useful for their data processing software and data products.  InSight Specific:  This is used primarily to indicate the actual parameters that were passed to the VICAR programs that created the image. Although it's likely any directory names specified do not exist in PDS, the filenames are more likely to be available. Primarily, the history label is preserved to document the processing parameters used.	1) name 2) proc:parameter_type 3) value 4) External_Reference	
parsing_standard_id	The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.	1)/Product Collection/File Area Inventory/Inventory/parsing standard 2)/Product Observational/File Area Observational/Table Delimited[*]	
		3)/Product_Observational/File_Area_Observational_Supplemental[1]/S	
		4)/Product_XML_Schema/File_Area_XML_Schema[*]/XML_Schema/parsing_standard_id	
		5)/Product_File_Text/File_Area_Text/Stream_Text/parsing_standard_id	
		6)/Product Observational/File Area Observational/Header/parsing standard id	
		1) 7-Bit ASCII Text 2) CDF 3.4 ISTP/IACG 3) FITS 3.0 4) ISIS2 5) ISIS2 History Label 6) ISIS3 7) PDS DSV 1 8) PDS ODL 2 9) PDS3 10) Pre-PDS3 11) UTF-8 Text 12) VICAR1 13) VICAR2	ASCII_Short_String_Collapsed
cart:Perspective	This is an in-situ projection that models a pinhole camera.	1)/Product Observational/Observation Area/Discipline Area/Cartogral System Definition/Local/Map Projection Lander/Perspective	ohy/Spatial Reference Information/Horizontal Coordinate
		1) <u>cart:pixel scale x</u> 2) <u>cart:pixel scale y</u> 3) <u>cart:maximum elevation</u> 4) <u>cart:start azimuth</u> 6) <u>cart:stop azimuth</u> 7) <u>cart:projection azimuth</u> 8) <u>cart:projection elevation</u> 9) <u>cart:Camera Model Offset</u>	
img:Pixel_Averaging_Dimensions		1)/Product Observational/Observation Area/Discipline Area/Imaging/	Downsampling/Pixel Averaging Dimensions

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
	The Pixel_Averaging class provides the height and width, in pixels, of the area over which pixels were averaged prior to image compression.	1) <u>img:height pixels</u> 2) <u>img:width pixels</u>		
cart:Pixel_Position_Origin	The Pixel_Position_Origin class specifies the sample coordinate of the location in the image of the "special" point of the mosaic. For Vertical, Orthographic and Orthorectified projections, this is the origin of the projected coordinate system, corresponding to the Vector_Projection_Origin. In PDS3, this information was specified using the LINE_PROJECTION_OFFSET and SAMPLE_PROJECTION_OFFSET keywords.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Vertical/Pixel Position Origin  2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Orthorectified/Pixel Position Origin  1) cart:line 2) cart:sample		
cart:pixel_scale_x	The pixel_scale_x and pixel_scale_y attributes indicate the image array pixel scale (pixel/degree or pixel/distance) relative to the Cartesian (x,y) coordinate system as defined by the map projection. Due to varying properties across different map projections, actual surface distances for an individual pixel may be accurate only at specific location(s) within the image array (e.g. reference latitude or longitude, standard parallels, etc). For most PDS products, x and y scale values are equal ('square' pixels). The inclusion of both x and y attributes allows for anticipated products where scale may differ for each axis ('rectangular' pixels). NOTE1: For presentation of hard-copy maps, a map scale is traditionally expressed as a 'representative fraction' (the ratio of a hard-copy map to the actual subject surface (e.g. 1:250,000, where one unit of measure on the map equals 250,000 of the same unit on the body surface)). This usage is relevant when map/data are presented on hard-copy media (paper, computer screen,etc). When defining pixel scale within a stored image/array context here, we are expressing a ratio between the image array and the actual surface (thus, pixel/degree or pixel/distance units). NOTE2: Definition of this PDS4 attribute differs from how 'scale' was defined within PDS3	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinates System Definition/Local/Map Projection Lander/Cylindrical/pixel scale x  2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinates System Definition/Local/Map Projection Lander/Perspective/pixel scale x  3)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinates System Definition/Local/Map Projection Lander/Cylindrical Perspective/pixel scale x  ASCII_Real  Units_of_Map_Scale		
cart:pixel_scale_y	The pixel_scale_x and pixel_scale_y attributes indicate the image array pixel scale (pixel/degree or pixel/distance) relative to the Cartesian (x,y) coordinate system as defined by the map projection. Due to varying properties across different map projections, actual surface distances for an individual pixel may be accurate only at specific location(s) within the image array (e.g. reference latitude or longitude, standard parallels, etc). For most PDS products, x and y scale values are equal ('square' pixels). The	System Definition/Local/Map Projection Lander/Cylindrical/pixel scale y  2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate		

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	inclusion of both x and y attributes allows for anticipated products where scale may differ for each axis ('rectangular' pixels). NOTE1: For presentation of hard-copy maps, a map scale is traditionally expressed as a 'representative fraction' (the ratio of a hard-copy map to the actual subject surface (e.g. 1:250,000, where one unit of measure on the map equals 250,000 of the same unit on the body surface)). This usage is relevant when map/data are presented on hard-copy media (paper, computer screen,etc). When defining pixel scale within a stored image/array context here, we are expressing a ratio between the image array and the actual surface (thus, pixel/degree or pixel/distance units). NOTE2: Definition of this PDS4 attribute differs from how 'scale' was defined within PDS3		ASCII_Real  Units_of_Map_Scale
Primary_Result_Summary	The Primary_Result_Summary class provides a high-level description of the types of products included in the collection or bundle	1)/Product Collection/Context Area/Primary Result Summary  2)/Product Observational/Observation Area/Primary Result Summary	
		1) type 2) purpose 3) data_regime 4) processina_level 5) processing_level_id 6) description 7) Science_Facets	
proc: <b>Process</b>	The Process class describes one of the software processes used to produce the data product referenced in the parent	1)/Product Observational/Observation Area/Discipline Area/Processing Information/Process	
	Processing_Information class. This class includes descriptions of the process owner as well as the data processing software used to create the data product.	1) <u>name</u> 2) <u>description</u> 3) <u>proc:process_owner_name</u> 4) <u>proc:process_owner_institution_name</u> 5) <u>proc:Software</u>	
img:processing_algorithm	The processing_algorithm attribute specifies the name of the algorithm used to perform the processing specified by the enclosing class. Algorithm names should be defined in the project documentation, and/or in the enclosing class definition.	by in the state of	
	InSight Specific: Insight uses 'Maki 2003'.		
			ASCII_Short_String_Collapsed
proc:Processing_Information	The Processing_Information class contains detailed information regarding the history of processing of the data product(s) described in the label. Information that can be specified using this class includes input products used to create a specific data product and the software and processes used to produce that product.	1)/Product Observational/Observation Area/Discipline Area/Processin  1) Local Internal Reference 2) proc:Input Product List	g Information
		3) <u>Process</u>	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
processing_level	The processing_level attribute provides a broad classification of data processing level.  InSight Specific:  A processing level of 'Raw' indicates an EDR; the others indicate an RDR.	1)/Product Collection/Context Area/Primary Result Summary/processing level  2)/Product Observational/Observation Area/Primary Result Summary/processing level	
		1) Calibrated 2) Derived 3) Partially Processed 4) Raw 5) Telemetry	ASCII_Short_String_Collapsed
	The Product Browse class defines a product consisting of one encoded byte stream digital object.  InSight Specific: On InSight, browse images are made for all products whose derived_image_type_name is 'IMAGE' (except for product type CNF, which are floating-point images not suitable for browse image creation).		
		1) Product 2) <u>Context Area</u> 3) <u>Identification Area</u> 4) <u>Reference List</u> 5) <u>File Area Browse</u>	
product_class	The product_class attribute provides the name of the product class.	1)/Product Collection/Identification Area/product class	
		2)/Product XML Schema/Identification Area/product_class	
		3)/Product_File_Text/Identification_Area/product_class	
		4)/Product Document/Identification Area/product class	
		5)/Product Observational/Identification Area/product class	
		6)/Product Browse/Identification Area/product class	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
		1) Product_AIP 2) Product_Actillary 3) Product_Attribute_Definition 4) Product_Browse 5) Product_Bundle 6) Product_Class_Definition 7) Product_Collection 8) Product_Context 9) Product_DIP 10) Product_DIP_Deep_Archive 11) Product_DIP_Deep_Archive 11) Product_Dit_Deep_Archive 11) Product_Dit_Ext 13) Product_File_Repository 14) Product_File_Text 15) Product_Instrument_Host_PDS3 16) Product_Instrument_PDS3 17) Product_Metadata_Supplemental 18) Product_Mission_PDS3 19) Product_Observational 21) Product_Observational 21) Product_SIP 23) Product_SIP_Deep_Archive 24) Product_SIP_CE_Kernel 25) Product_Software 27) Product_Software 27) Product_Subscription_PDS3 28) Product_Target_PDS3 29) Product_Tupdate 31) Product_Volume_PDS3 32) Product_Volume_PDS3 33) Product_Volume_Set_PDS3 33) Product_Volume_Set_PDS3 33) Product_Zipped	ASCII_Short_String_Collapsed
Product_Collection	A Product_Collection has a table of references to one or more basic products. The references are stored in a table called the inventory.	1) Product 2) Identification Area 3) Context Area 4) Reference List 5) Collection 6) File Area Inventory	
Product_Document	A Product Document is a product consisting of a single logical document that may comprise one or more document editions.	1) Product 2) Identification Area 3) Context Area 4) Reference List 5) Document	
Product_File_Text	The Product File Text consists of a single text file with ASCII character encoding.	1) Product 2) Identification Area 3) Reference List 4) File Area Text	

Dictionary:PDS4 Keyword	General Definition	XPath		
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units	
Product_Observational	A Product_Observational is a set of one or more			
	information objects produced by an observing system.	1) Product 2) Identification_Area 3) Observation_Area 4) Reference_List 5) File_Area_Observational 6) File_Area_Observational_Supplemental		
msn:product_type_name	The product_type_name identifies a group of data products within a collection that have some property in			
	common, such as processing level, resolution, or instrument-specific setting.  InSight Specific:  This corresponds to the EDR/RDR Product Types defined in Table 4-4 in the SIS and used as identifiers throughout.		ASCII_Short_String_Collapsed	
Product_XML_Schema				
	the PDS4 implementation into XML.	1) Product 2) <u>Context Area</u> 3) <u>Identification Area</u> 4) <u>Reference List</u> 5) <u>File Area XML Schema</u>		
proc: <b>program_type_name</b>	The program_type_name attribute specifies the type of software program used for this software processing. Some examples include: VICAR, ISIS, GDAL.	1)/Product Observational/Observation Area/Discipline Area/Processing ogram type name	ng Information/Process/Software/Software Program[*1/pr	
		2)/Product Observational/Observation Area/Discipline Area/Processing am type name	ng Information/Process/Software/Software Program/progr	
			ASCII_Short_String_Collapsed	
publication_date	The publication_date attribute provides the date on which an item was published.	1)/Product Document/Document/publication date		
	an item was published.		ASCII_Date_YMD	
publication_year	The publication_year attribute provides the year in which the product should be considered as published. Generally,	1)/Product Collection/Identification Area/Citation Information/publication year		
	this will be the year the data were declared "Certified" or "Archived".	2)/Product File Text/Identification Area/Citation Information/publication year		
3)/Product_Document/Identification_Area/Citation_Information/publication_year		cation_year		
			ASCII_Date_YMD	
purpose  The purpose attribute provides an indication of the primary purpose of the observations included.  1)/Product Collection/Context Area/Primary Result Summary/purpose		<u>e</u>		
	InSight Specific:	2)/Product Observational/Observation Area/Primary Result Summary	// <u>purpose</u>	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	Products coming from the InSight pipeline are always marked as Science.	1) Calibration 2) Checkout 3) Engineering 4) Navigation 5) Observation Geometry 6) Science	ASCII_Short_String_Collapsed
geom:Quaternion_Model_Transform	The Quaternion_Model_Transform class specifies, along with Vector_Model_Transform class, the transform used	1)/Product_Observational/Observation_Area/Discipline_Area/Geometro on_Model_Transform	y/Geometry_Lander/Camera_Model_Parameters/Quaterni
	for the camera model in an image. Camera models created by the calibration process have associated with them a pose, comprised of the position (offset) and orientation (quaternion) of the camera at the time it was calibrated. The model is transformed ("pointed") for a specific image by computing, generally using articulation device kinematics, a final pose for the image. The camera model is then translated and rotated from the calibration to final pose. This class specifies the quaternion portion of the final pose.  InSight Specific:  The calibration pose is in NSYT_idc.point in the calibration collection.	1) <u>geom:qsin1</u> 3) <u>geom:qsin2</u> 4) <u>geom:qsin3</u>	
img:Radiometric_Correction	The Radiometric_Correction class is a container for the type and details of the radiometric calibration performed	1)/Product Observational/Observation Area/Discipline Area/Imaging/Radiometric Correction	
	on the product.	1) img:active flag 2) img:radiometric type 3) img:processing venue 4) img:radiometric zenith scaling factor 5) img:processing algorithm 6) img:responsivity_r 7) img:sequence_number 8) img:responsivity_g 9) img:responsivity_b 10) img:responsivity_pan 11) comment 12) img:Data_Processing	
img:radiometric_zenith_scaling_factor	Defines the scaling factor used for Scaled Radiance or Scaled Spectral Radiance. Scaled radiance is created by	1)/Product Observational/Observation Area/Discipline Area/Imaging/Radiometric Correction/radiometric zenith scaling factor	
	dividing radiance by this factor, which scales the radiance to what it would be if the sun were at the zenith with a clear atmosphere.		ASCII_Real
Record_Delimited	The Record_Delimited class is a component of the delimited table (spreadsheet) class and defines a record of the delimited table.	f 1)/Product_Collection/File_Area_Inventory/Inventory/Record_Delimited	
	The definited table.	2)/Product Observational/File Area Observational/Table Delimited[*]	/Record_Delimited
		1) fields 2) maximum_record_length 3) groups 4) Field_Delimited	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
record_delimiter	The record_delimiter attribute provides the character or characters used to indicate the end of a record.	1)/Product Collection/File Area Inventory/Inventory/record delimiter	
		2)/Product Observational/File Area Observational/Table Delimited[*]/record delimiter	
		3)/Product Observational/File Area Observational Supplemental[1]/S	itream_Text/record_delimiter
		4)/Product File Text/File Area Text/Stream Text/record_delimiter	
		Carriage-Return Line-Feed     Carriage-return line-feed	ASCII_Short_String_Collapsed
records	The records attribute provides a count of records.	1)/Product_Collection/File_Area_Inventory/File/records	
		2)/Product_Collection/File_Area_Inventory/Inventory/records	
		3)/Product Observational/File Area Observational/Table Delimited[*]/records	
		4)/Product XML Schema/File Area XML Schema[*]/File/records	
			ASCII_NonNegative_Integer
disp:red_channel_band	The red_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by	1)/Product Observational/Observation Area/Discipline Area/Display	Settings/Color Display Settings/red channel band
	default, into the red channel of a display device. The first band along the band axis has band number 1.		ASCII_Integer
Reference_List	The Reference_List class provides general references, cross-references, and source products for the product.	1)/Product Collection/Reference List	
	References cited elsewhere in the label need not be repeated here.  InSight Specific:	2)/Product_File_Text/Reference_List	
	This is used to point to the browse image (if it exists), as well as the source products (EDRs or Raw products) that	3)/Product Document/Reference List	
were used to make this derived product. Note that EDRs refer to themselves as a source product.		4)/Product Observational/Reference List	
		5)/Product_Browse/Reference_List	
		1) <u>Internal Reference</u> 2) External_Reference 3) Source Product Internal	
		4) Source_Product_External	

reference_type	The reference_type attribute provides the name of the association.	1)/Product Collection/Context Area/Investigation Area/Internal Reference/reference type
		2)/Product Collection/Context Area/Observing System/Observing System Component[*]/Internal Reference/reference type
		3)/Product Collection/Context Area/Target Identification/Internal Reference/reference type
		4)/Product_Collection/Reference_List/Internal_Reference[*]/reference_type
		5)/Product_Collection/File_Area_Inventory/Inventory/reference_type
		6)/Product File Text/Reference List/Source Product Internal[*]/reference type
		7)/Product Document/Reference List/Internal Reference[*]/reference type
		8)/Product Document/Context Area/Investigation Area/Internal Reference/reference type
		9)/Product Document/Context Area/Observing System/Observing System Component/Internal Reference/reference type
		10)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Geometry Projection/Internal Reference/reference type
		11)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Stereo Product Parameters/Internal Reference/reference type
		12)/Product_Observational/Observation_Area/Discipline_Area/Processing_Information/Input_Product_List/Input_Product[*]/Inter_nal_Reference/reference_type
		13)/Product Observational/Observation Area/Discipline Area/Surface Imaging/Derived Product Parameters/Placement Target Instrument/Internal Reference/reference_type
		14)/Product Observational/Reference List/Source Product Internal[*]/reference type
		15)/Product Observational/Observation Area/Discipline Area/Imaging/Flat_Field_Correction/Flat_Field_File/Internal_Reference/reference_type
		16)/Product Observational/Observation Area/Discipline Area/Processing Information/Input Product List/Input Product/Interna   Reference/reference_type
		17)/Product Observational/Observation Area/Investigation Area/Internal Reference/reference type
		18)/Product Observational/Observation Area/Observing System/Observing System Component[*]/Internal Reference/reference type
		19)/Product Observational/Observation Area/Target Identification/Internal Reference/reference type
		20)/Product Observational/Reference List/Internal Reference/reference type
		21)/Product Observational/Reference List/Source Product Internal/reference type
		22)/Product Browse/Reference List/Internal Reference/reference type

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
			ASCII_Short_String_Collapsed
geom: <b>rotation_direction</b>	The rotation_direction attribute identifies the direction of the rotation for a specific quaternion. This is used when the two frames involved are unambiguously identifed in	1)/Product Observational/Observation Area/Discipline Area/Geome ernion Plus Direction/rotation direction	try/Geometry_Lander/Coordinate_Space_Definition[*]/Quat
	the enclosing classes.  InSight Specific:  In the context of a coordinate frame definition, 'Forward' means that given a vector expressed in the current ('present') frame, multiplication by the quaternion will give the same vector as expressed in the reference frame.	1) Present to Reference 2) Reference to Present 3) Forward 4) Reverse 5) From Base 6) Toward Base	ASCII_Short_String_Collapsed
cart: <b>sample</b>	The sample attribute specifies the sample number.	1)/Product Observational/Observation Area/Discipline Area/Cartogr System Definition/Local/Map Projection Lander/Vertical/Pixel Pos	aphy/Spatial Reference Information/Horizontal Coordinate tition Origin/sample
		2)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Orthorectified/Pixel Position Origin/sample	
		3)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Perspective/Camera Model Offset/sample	
			ASCII_Real
img:Sampling	The Sampling class contains attributes and classes related to the sampling, scaling, companding, and compression or	1)/Product Observational/Observation Area/Discipline Area/Imaging/Sampling	
	reduction in resolution of data.	1) img:crosstrack_summing 2) img:downtrack_summing 3) img:sample_bits 4) img:sample_bit_mask 5) img:sampling_factor 6) img:Companding	
Science_Facets	The Science_Facets class contains the science-related search facets. It is optional and may be repeated if an product has facets related to, for example, two different	1)/Product_Collection/Context_Area/Primary_Result_Summary/Science_Facets	
	disciplines (as defined by the discipline_name facet). Note that Science_Facets was modeled with Discipline_Facets as	2)/Product Observational/Observation Area/Primary Result Summary/Science Facets	
	a component and Discipline_Facets was modeled with Group_Facet1 and Group_Facet2 as components. This dependency hierarchy was flattened and only Science_Facets exists in the schema.	1) <u>wavelength range</u> 2) <u>domain</u> 3) Discipline_Facets 4) discipline_name	
msn_surface: <b>sequence_id</b>	The sequence_id identifies the command sequence used to acquire this product.	ed .	
	to acquire this product.		ASCII_Short_String_Collapsed
sequence_number	The sequence_number attribute provides a number that is used to order axes in an array.	1)/Product Observational/File Area Observational/Array 2D Image/Axis Array[*]/sequence number	
		2)/Product Observational/File Area Observational/Array 3D Image/Axis Array[*]/sequence number	
			ASCII_NonNegative_Integer

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
img:Shutter_Subtraction	The Shutter_Subtraction class specifies attributes describing the removal from the image of the shutter, or fixed-pattern.	1)/Product Observational/Observation Area/Discipline Area/Imaging/Shutter Subtraction	
		2)/Product Observational/Observation Area/Discipline Area/Imaging/	Commanded_Parameters/Shutter_Subtraction
		1) img:active flag 2) img:shutter subtraction mode 3) img:processing venue 4) img:exposure_duration_threshold_count 5) img:processing algorithm 6) img:sequence_number 7) img:Data_Processing	
proc: <b>Software</b>	The Software class describes the data processing software used in order to produce the data product.	1)/Product Observational/Observation Area/Discipline Area/Processing	ng Information/Process/Software
	disca in order to produce the data product.	1) name 2) software_id 3) software_version_id 4) software_type 5) description 6) Internal Reference 7) proc:Software Program	
proc:Software_Program	The Software_Program class describes the specific components or tasks of the Software executed in producing the data product.  InSight Specific:  When used to document the VICAR processing history, multiple instances of Software_Program show the different programs that have been run on the data, in the order they were run.	1)/Product Observational/Observation Area/Discipline Area/Processing Information/Process/Software/Software Program[*]	
		2)/Product Observational/Observation Area/Discipline Area/Processing Information/Process/Software/Software Program	
W m pr		1) name 2) proc:program_type_name 3) proc:program_user 4) proc:program_hostname 5) proc:program_path 6) proc:program_version 7) proc:program_start_date_time 8) proc:program_stop_date_time 9) description 10) proc:Software_Program_Parameters	
proc:Software_Program_Parameters	The Software_Program_Parameters class specifies the set of 1 or more parameters for the software program. These parameters can be input, output, or log information. The	1)/Product Observational/Observation Area/Discipline Area/Processing ftware Program Parameters	ng Information/Process/Software/Software Program[*]/So
	premise being a way to capture as much information as possible about the software program execution.	2)/Product_Observational/Observation_Area/Discipline_Area/Processir ware_Program_Parameters	ng_Information/Process/Software/Software_Program/Soft
		1) proc:Parameter	
Source_Product_Internal	The Source_Product _Internal class is used to reference one or more source products in the PDS4 registry system. A source product contains input data for the creation of this product.	1)/Product File Text/Reference List/Source Product Internal[*] 2)/Product Observational/Reference List/Source Product Internal[*]	
		3)/Product_Observational/Reference_List/Source_Product_Internal	
		1) lidvid reference 2) reference type 3) comment	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Spatial_Reference_Information class provides a description of the reference frame for, and the means to	1)/Product_Observational/Observation_Area/Discipline_Area/Cartography/Spatial_Reference_Information	
	encode, coordinates in a data set.	1) <u>cart:Horizontal Coordinate System Definition</u>	
Special_Constants	The Special Constants class provides a set of values used to indicate special cases that occur in the data.	1)/Product Observational/File Area Observational/Array 2D Image/Special Constants	
		2)/Product Observational/File Area Observational/Array 3D Image/Special Constants	
		1) saturated_constant 2) missing_constant 3) error_constant 4) invalid_constant 5) unknown_constant 6) not_applicable_constant 7) valid_maximum 8) high_instrument_saturation 9) high_representation_saturation 10) valid_minimum 11) low_instrument_saturation 12) low_representation_saturation	
geom:SPICE_Kernel_Files	The SPICE_Kernel_Files class provides references to the SPICE files used when calculating geometric values.	1)/Product Observational/Observation Area/Discipline Area/Geometr	y/SPICE Kernel Files
		1) <u>comment</u> 2) <u>geom:SPICE Kernel Identification</u>	
geom:SPICE_Kernel_Identification	The SPICE_Kernel_Identification class optionally includes the SPICE kernel type and provides two alternatives for	1)/Product Observational/Observation Area/Discipline Area/Geometry/SPICE Kernel Files/SPICE Kernel Identification	
identifying the product: and the file name of the LIDVID should be given kernel_provenance attr is a predict or reconstru of the two, or if it is a ke	identifying the product: LIDVID using Internal_Reference, and the file name of the kernel file. Although optional, LIDVID should be given if one is available. The optional kernel_provenance attribute indicates whether the kernel is a predict or reconstructed kernel, or some combination of the two, or if it is a kernel type for which such distinctions do not apply.	1) kernel_type 2) geom:spice kernel file name 3) geom:kernel_provenance 4) Internal Reference	
msn:start_local_mean_solar_time_sol	The start_local_mean_solar_time_sol element specifies the number of solar days elapsed since a reference day		
	(e.g. the day on which a landing vehicle set down) for local mean solar time (LMST). Days are measured in rotations of the planet in question from midnight to midnight. The reference day is '0', as Landing day is Sol 0. If before Landing day, then value will be less than or equal to '0' and can be negative.  InSight Specific:  Note that this sol value can be different from the sol (start_sol_number), which is derived from local_true_solar_time.		ASCII_Integer
img_surface: <b>stereo_baseline_length</b>	The stereo_baseline_length attribute specifies the separation between the two cameras used for processing		
	separation between the two cameras used for processing of the stereo image.		ASCII_Real
			Units_of_Length
img_surface: <b>Stereo_Product_Parameters</b>			

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Stereo_Product_Parameters class describes the conditions under which stereo analysis was performed. This includes items such as the stereo baseline (separation between the cameras) and what partner image(s) were used for stereo analysis. If present, stereo partner images can be referenced using either an Internal_Reference or External_Reference.	1) <u>img surface:stereo baseline length</u> 2) External_Reference	
Stream_Text	The Stream text class defines a text object.	1)/Product Observational/File Area Observational Supplemental[1]/S	tream_Text
		2)/Product File Text/File Area Text/Stream Text	
		1) name 2) offset 3) record delimiter 4) local identifier 5) object_lenath 6) md5_checksum 7) description 8) parsing standard id 9) Parsable_Byte_Stream 10) Digital_Object	
img:Subframe	The Subframe class describes the position and other optional characteristics of an image subframe, relative to	1)/Product Observational/Observation Area/Discipline Area/Imaging/	<u>Subframe</u>
	the original image.	1) ima:first_line 2) ima:first_sample 3) ima:lines 4) ima:samples 5) ima:line_fov 6) ima:sample_fov 7) name 8) description 9) ima:subframe_type	
img_surface:Surface_Imaging	Attributes specific to imaging instruments on surface missions.		
		1) ima surface:Image Identifiers 2) ima surface:Instrument Information 3) ima surface:Derived Product Parameters 4) ima surface:Error Model 5) ima surface:Geometry Projection 6) ima surface:Stereo Product Parameters 7) geom:Coordinate Space Reference 8) ima_surface:Error_Pixel	
msn: <b>Surface_Mission</b>			

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	The Surface_Mission class provides information about a surface mission.	1) msn:start sol number 2) msn:start local mean solar time 4) msn:stop_local_mean_solar_time 5) msn:start local mean solar time sol 6) msn:start local mean_solar_time_sol 7) msn:start local true solar time 8) msn:stop_local_true_solar_time 9) msn:start local true solar_time 9) msn:start local true solar_time 10) msn:stop_local_true_solar_time_sol 11) msn:solar_lonaitude	
msn_surface:Surface_Mission_Information	The Surface_Mission_Information class contains attributes specific to surface missions which apply across instrument		
	types.	1) msn surface:surface gravity 2) msn surface:Command Execution 3) msn surface:Telemetry	
cart:Surface_Model_Parameters	null	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate  System Definition/Local/Surface Model Parameters	
		1) <u>cart:Surface model type</u> 2) <u>cart:Surface Model Planar</u> 3) <u>geom:Coordinate Space Reference</u>	
cart:Surface_Model_Planar	null	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Surface Model Parameters/Surface Model Planar	
		1) <u>cart:Vector Surface Normal</u> 2) <u>cart:Vector Surface Ground Location</u>	
Table_Delimited  The Table_Delimited class defines a simple table (spreadsheet) with delimited fields and records.		1)/Product Observational/File Area Observational/Table Delimited[*]	
		1) name 2) offset 3) records 4) local identifier 5) object lenath 6) record delimiter 7) md5_checksum 8) parsing standard id 9) description 10) field delimiter 11) Parsable_Byte_Stream 12) Digital_Object 13) Uniformly_Sampled 14) Record_Delimited	
Target_Identification	The Target_Identification class provides detailed target identification information.	1)/Product Collection/Context Area/Target Identification	
		2)/Product Observational/Observation Area/Target Identification	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
		1) <u>name</u> 2) alternate_designation 3) <u>type</u> 4) <u>description</u> 5) <u>Internal_Reference</u>	
msn_surface: <b>Telemetry</b>	The Telemetry class contains downlink-related attributes used primarily during mission operations.		
		1) msn surface:application_id 2) msn_surface:application_subtype_id 3) msn surface:application_name 4) msn surface:provider_id 5) msn surface:flight_software_version_id 6) msn surface:telemetry_source_name 7) msn surface:telemetry_rource_name 7) msn surface:communication_session_id 9) msn surface:telemetry_source_start_time 10) msn surface:telemetry_source_stlk_start 11) msn surface:product_completion_status 12) msn surface:earth_received_start_date_time 13) msn surface:earth_received_stop_date_time 14) msn surface:download_priority 15) msn surface:download_priority 16) msn surface:expected_packets 17) msn surface:received_packets	
Time_Coordinates	The Time_Coordinates class provides a list of time coordinates.	1)/Product_Collection/Context_Area/Time_Coordinates	
		2)/Product Observational/Observation Area/Time Coordinates  1) start date time 2) stop date time 3) local mean solar time 4) local true solar time 5) solar longitude	
title	The name given to the resource. Typically, a Title will be a name by which the resource is formally known Dublin Core - The title is used to refer to an object in a version independent manner.	1)/Product Collection/Identification Area/title 2)/Product XML Schema/Identification Area/title	
		3)/Product File Text/Identification Area/title	
		4)/Product Document/Identification Area/title	
		5)/Product_Observational/Identification_Area/title	
		6)/Product_Browse/Identification_Area/title	
			UTF8_Short_String_Collapsed

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
type	The type attribute classifies Investigation_Area according to the scope of the investigation	1)/Product Collection/Context Area/Investigation Area/type	
		2)/Product Collection/Context Area/Observing System/Observing System Component[*]/type	
		3)/Product Collection/Context Area/Target Identification/type  4)/Product Document/Context Area/Investigation Area/type  5)/Product Document/Context Area/Observing System/Observing System Component/type  6)/Product Observational/Observation Area/Investigation Area/type	
		7)/Product_Observational/Observation_Area/Observing_System_Component[*]/type	
		8)/Product Observational/Observation Area/Target Identification/type	
		1) Individual Investigation     2) Mission     3) Observing Campaign     4) Other Investigation	ASCII_Short_String_Collapsed
geom:Vector_Device_Gravity	The Vector_Device_Gravity class is a unit vector that specifies the direction of an external force acting on the articulation device, in the spacecraft's coordinate system,	external force acting on the ctor Device Gravity	
	at the time the pose was computed.	1) geom:x unit 2) geom:y unit 3) geom:z unit 4) geom:Vector_Cartesian_Unit	
geom:Vector_Model_Transform  The Vector_Model_Transform class specifies, along with the Quaternion_Model_Transform class, the transform used for the camera model in this image. Camera models		1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/Vector  Model Transform	
	created by the calibration process have associated with them a pose, comprised of the position (offset) and orientation (quaternion) of the camera at the time it was calibrated. The model is transformed ("pointed") for a specific image by computing, generally using articulation device kinematics, a final pose for the image. The camera model is then translated and rotated from the calibration to final pose. This class specifies the offset portion of the final pose.  InSight Specific:  The calibration pose is in NSYT_idc.point in the calibration collection.	1) geom:x 2) geom:y 3) geom:z 4) geom:Vector_Cartesian_No_Units	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type <i>Units</i>
version_id	The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.  InSight Specific:  On InSight, the version is always x.0 where x matches the operations version at the end of the filename. Thus	1)/Product Collection/Identification Area/version id	
		2)/Product Collection/Identification Area/Modification History/Modification Detail/version id	
	versions may not start at 1.0 and version numbers may be skipped.	3)/Product_XML_Schema/Identification_Area/version_id	
		4)/Product_XML_Schema/Identification_Area/Modification_History/Modification_Detail/version_id  5)/Product_Document/Identification_Area/Modification_History/Modification_Detail/version_id	
	6)/Product File Text/Identification Area/version		
		7)/Product Document/Identification Area/version id  8)/Product Observational/Identification Area/version id  9)/Product Browse/Identification Area/version id	
			ASCII_Short_String_Collapsed
cart: <b>Vertical</b>	This is an in-situ projection that provides an overhead view. By projecting to a surface model, the need for range data is eliminated, but significant layover effects can happen when the actual geometry does not match the surface model. It has a constant scale in meters/pixel, subject to layover distortion.	1)/Product Observational/Observation Area/Discipline Area/Cartography/Spatial Reference Information/Horizontal Coordinate System Definition/Local/Map Projection Lander/Vertical	
		1) cart:pixel resolution x 2) cart:pixel resolution y 3) cart:x axis maximum 4) cart:x axis minimum 5) cart:y axis maximum 6) cart:y axis minimum 7) cart:Pixel Position Origin 8) cart:Vector Projection Origin	
disp:vertical_display_axis	The vertical_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be	1)/Product Observational/Observation Area/Discipline Area/Display Settings/Display Direction/vertical display axis	
	displayed in the vertical or "line" dimension on a display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.		ASCII_Short_String_Collapsed
disp:vertical_display_direction	The vertical_display_direction attribute specifies the direction along the screen of a display device that data	1)/Product_Observational/Observation_Area/Discipline_Area/Display_Settings/Display_Direction/vertical_display_direction	
	along the vertical axis of an Array is supposed to be displayed.	1) Bottom to Top 2) Top to Bottom	ASCII_Short_String_Collapsed
wavelength_range	The wavelength range attribute specifies the wavelength range over which the data were collected or which	th 1)/Product Collection/Context Area/Primary Result Summary/Science Facets/wavelength range	
otherwise characterizes the observation(s). Boundaries are		2)/Product Observational/Observation Area/Primary Result Summary/Science Facets/wavelength range	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
	vague, and there is overlap. InSight Specific: For InSight cameras the value is always Visible.	1) Far Infrared 2) Gamma Ray 3) Infrared 4) Microwave 5) Millimeter 6) Near Infrared 7) Radio 8) Submillimeter 9) Ultraviolet 10) Visible 11) X-ray	ASCII_Short_String_Collapsed
geom: <b>x_pixel</b>	The x component of a Cartesian pixel vector; typically used in cameral models.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE Model/Vector Horizontal/x pixel  2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE Model/Vector Vertical/x pixel  3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV M odel/Vector Horizontal/x pixel  4)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV M odel/Vector Vertical/x pixel  5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Horizontal/x pixel	
			ASCII_Real
XML_Schema	The XML Schema class defines a resource used for the PDS4 implementation into XML.	1)/Product XML Schema/File Area XML Schema(*)/XML Schema	
		1) name 2) offset 3) parsing standard id 4) local identifier 5) object length 6) Idd_version_id 7) md5_checksum 8) description 9) Parsable_Byte_Stream 10) Digital_Object	

Dictionary:PDS4 Keyword	General Definition	XPath	
VICAR Property. <b>VICAR Keyword</b>	InSight-Specific Information	Valid Values (attribute) Children (class)	Data Type Units
geom: <b>y_pixel</b>	The y component of a Cartesian pixel vector; typically used in cameral models.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORIModel/Vector Horizontal/y pixel	
		2)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE Model/Vector Vertical/y pixel	
		3)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHV Model/Vector Horizontal/y pixel	
		4)/Product_Observational/Observation_Area/Discipline_Area/Geometry/Geometry_Lander/Camera_Model_Parameters/CAHV_Model/Vector_Vertical/y_pixel	
		5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Horizontal/y pixel	
		6)/Product Observational/Observation Area/Discipline Area/Geometre Model/Vector Vertical/y pixel	y/Geometry Lander/Camera Model Parameters/CAHVOR
			ASCII_Real
geom: <b>z_pixel</b>	The z component of a Cartesian pixel vector; typically used in cameral models.	1)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVORE  _Model/Vector Horizontal/z pixel	
		2)/Product Observational/Observation Area/Discipline Area/GeometreModel/Vector Vertical/z_pixel	y/Geometry Lander/Camera Model Parameters/CAHVORE
		3)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Horizontal/z_pixel	y/ <u>Geometry Lander/Camera Model Parameters/CAHV M</u>
		4)/Product Observational/Observation Area/Discipline Area/Geometrodel/Vector Vertical/z pixel	y/ <u>Geometry Lander/Camera Model Parameters/CAHV M</u>
		5)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Horizontal/z pixel  6)/Product Observational/Observation Area/Discipline Area/Geometry/Geometry Lander/Camera Model Parameters/CAHVOR Model/Vector Vertical/z pixel	
			ASCII_Real